

Technical Data Sheet

Page 1 of 1

- Properties:** AKEMI® PU Primer Black is a solvent-containing, physically and reactively drying black primer for polyurethane adhesives for use on glass.
- The product is characterized by the following properties:
- very good covering power
 - excellent adhesion on glass and ceramics
 - UV-protection for windscreen sealant
 - fast drying
- Application Area:** Used to protect the bondline from UV and increase the bond strength of adhesives to windscreens and for repairing damaged ceramic coatings.
- Instructions for Use:**
1. Surfaces must be clean, dry and free of dust and grease.
 2. Shake can thoroughly before use.
 3. Apply the product with a primer brush or wool wiper all around the edge of the windscreen.
 4. Allow to dry for approx. 10 minutes before applying the adhesive.
 5. Use up opened containers within a few days.
- Special Notes:**
- For professional use only.
 - Attention: contains diisocyanates. May cause an allergic reaction. As from August 24, 2023, adequate training is required before industrial or commercial use.
 - For proper waste disposal the container must be completely emptied.
 - Recycling in accordance with the guidelines of EU Decision 97/129 EC on the Packaging Directive 94/62/EC.
- Technical Data:**
- | | |
|----------------------|-------------------------------|
| Base: | reactive polyurethane adducts |
| Colour: | black |
| Consistency: | liquid |
| Density: | 0.95 g/ml |
| Working temperature: | 10°C - 35°C |
| VOC: | 588.1 g/l |
- Storage:** If stored in dry and cool condition (5-25°C/41-77°F) in its closed original container at least 12 months from production.
- Health & Safety:** Read Safety Data Sheet before handling or using this product.
- Important Notice:** The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trails of the product, in an inconspicuous area or fabrication of a sample piece.

TDS 07.25