

Technical Data Sheet

Page 1 of 2

- Properties:** AKEMI® Spray Transparent Grease 3 is a calcium-based multi-purpose grease thickened to low viscosity with organic clay.
- The product is characterized by the following properties:
- free of silicone
 - resin-free
 - cold, warm and sea water resistant
 - high pressure resistance
 - retains properties over a wide temperature range
 - acid-free
 - excellent protection against corrosion and oxidation
 - will not harm rubber and plastic or swell nylon
 - sprays in any angle
- Application Area:** AKEMI® Spray Transparent Grease 3 is most commonly used during vehicle, trucks, caravans and marine servicing as well as for many industrial applications. The product covers a wide application area and thus replaces many conventional greases. Both the high pressure and the anti-wear resistance make the product suitable for mechanical applications under high load stress. Excellent lubricating properties that protect against oxidation and salt-water corrosion. Spray Transparent Grease 3 is ideal for the lubrication of sliding and roller bearings, ball joints, chassis and all highly stressed parts on cars and trucks, transportation, agriculture, industry, marine and for off-road vehicles.
- The product is widely used for lubricating:
- door locks, hinges and check straps
 - window regulators
 - bonnet catches and hinges
 - support wheels, support legs and locking catches on caravans
 - rigging bolts and hinges on boats
 - door hinges
- Instructions for Use:**
1. Shake well before use.
 2. Spray directly onto moving parts of the component requiring lubricating from a distance of 20 to 30 cm.
- Special Notes:**
- For professional use only.
 - For proper waste disposal, the container must be completely emptied.
 - Recycling in accordance with the guidelines of EU Decision 97/129 EC on the Packaging Directive 94/62/EC.
- Technical Data:**
- | | |
|--------------------|-------------------|
| Colour: | milky transparent |
| Temperature range: | -20°C up to 160°C |
- Storage:** If stored in dry and cool condition (5-25°C/41-77°F) in its closed original container at least 12 months from production.
- Health & Safety:** Read Safety Data Sheet before handling or using this product.

TDS 11.25

Technical Data Sheet

Page 2 of 2

Important Notice:

The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trials of the product, in an inconspicuous area or fabrication of a sample piece.