

Technical Data Sheet

Page 1 of 2

Properties:	AKEMI® Brake Caliper Spray is a high-quality, solvent containing 1-component lacquer. The product is characterized by the following properties: <ul style="list-style-type: none">- fast drying- very good adhesion on iron, steel, wood, light metal- weather-resistant, non-yellowing- high surface hardness, but at the same time good elasticity- resistant against petrol and thawing salt, car wash resistant						
Application Area:	AKEMI® Brake Caliper Spray is used to emphasize the brake calipers by means of colour, especially on sport wheel rims.						
Instructions for Use:	<ol style="list-style-type: none">1. Jack the vehicle in accordance with the manufacturer's instructions and remove the wheel.2. Remove all rust, oil and grease from the calipers, clean them thoroughly and let them dry.3. Cover up surfaces which are not to be painted (e.g. brake disc, brake pads, brake hoses).4. Prime the surface using AKEMI® Primer Spray light grey; optimum working temperature 15 - 25°C.5. Shake the can well before use for several minutes after hearing the balls rattle).6. Spray a thin layer in a criss-cross pattern and in short bursts at a distance of 25 cm. If necessary, spray several layers. Optimum working temperature 15 - 25°C.7. Dust no longer clings to the paint layer after approx. 10 minutes, after approx. 30 minutes it is dry enough to be touched.						
Special Notes:	<ul style="list-style-type: none">- For professional use only.- Do not use at too high temperatures or in intense sunlight because the paint would dry too quickly and does not run properly (formation of blooming). Optimum working temperature 15 - 25°C.- Drying is far better if the product is applied in several layers rather than one thick one.- It is not necessary to empty the spray nozzle when you have finished your work.- Areas which have been sprayed accidentally can be cleaned with AKEMI® Universal Thinner.- For proper waste disposal, the container must be completely emptied.- Recycling in accordance with the guidelines of EU Decision 97/129 EC on the Packaging Directive 94/62/EC.						
Technical Data:	<table><tr><td>Colour:</td><td>red</td></tr><tr><td>Drying:</td><td>dust-dry after approx. 10 min touch-dry after approx. 25 min dry to the grip after approx. 30 min completely dry after approx. 2 hours</td></tr><tr><td>Coverage:</td><td>up to 2 brake calipers per spray can</td></tr></table>	Colour:	red	Drying:	dust-dry after approx. 10 min touch-dry after approx. 25 min dry to the grip after approx. 30 min completely dry after approx. 2 hours	Coverage:	up to 2 brake calipers per spray can
Colour:	red						
Drying:	dust-dry after approx. 10 min touch-dry after approx. 25 min dry to the grip after approx. 30 min completely dry after approx. 2 hours						
Coverage:	up to 2 brake calipers per spray can						
Storage:	If stored in dry and cool condition (5-25°C/41-77°F) in its closed original container at least 36 months from production.						
Health & Safety:	Read Safety Data Sheet before handling or using this product.						

TDS 11.25

Technical Data Sheet

Page 2 of 2

Important Notice:

The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trials of the product, in an inconspicuous area or fabrication of a sample piece.