

Technical Data Sheet

Page 1 of 2

Properties:	<p>AKEMI® Primer Spray is a high-quality, 1-component paint which contains solvents.</p> <p>The product is characterized by the following properties:</p> <ul style="list-style-type: none">- fast-drying- very good adhesion on iron, steel or wood resp. adhesion promoter between surface and paint- good covering properties- free of heavy metals- high filling power								
Application Area:	<p>AKEMI® Primer Spray is used as surface layer respectively adhesion promoter when repairing defects in paint work on car bodies and other objects made of steel and aluminum.</p>								
Instructions for Use:	<ol style="list-style-type: none">1. The surface must be free of rust and grease, thoroughly cleaned, dry and slightly roughened.2. Mask parts which are not to be sprayed or cover with paper.3. Shake the spray can well for several minutes before use after hearing the mixing balls.4. Apply 2 thin layers (at a spraying distance of approx. 25 cm and at intervals of 3 - 5 minutes).5. After drying (approx. 2 - 4 hours) the surface can be ground wet with grinding paper P600 (pay attention to a good transition), then clean the surface and let it dry.6. The product can be painted with AKEMI® Paint Sprays; when using different paint systems make a preliminary test first.								
Special Notes:	<ul style="list-style-type: none">- For professional use only.- Do not use at too high temperatures or in intense sunlight, as the paint dries too quickly and does not run properly (blooming). Optimum working temperature: 15 - 25°C.- Drying is far better if the product is applied in several thin layers rather than one thick one.- The degree of gloss is clearly diminished when the top coat is painted wet-in-wet.- It is not necessary to empty the spray nozzle when you have finished your work.- Areas which have accidentally been sprayed can be cleaned with AKEMI® Universal Thinner (check the compatibility).- Not suited in combination with polyester fillers and 2-component paints.- For proper waste disposal the container must be completely emptied.- Recycling in accordance with the guidelines of EU Decision 97/129 EC on the Packaging Directive 94/62/EC.								
Technical Data:	<table><tr><td>Colour:</td><td>light grey</td></tr><tr><td>Density:</td><td>approx. 0.8 g/cm³</td></tr><tr><td>Drying:</td><td>dust-dry after approx. 30 minutes touch-dry after approx. 50 minutes polishable after approx. 2 - 4 hours</td></tr><tr><td>Coverage:</td><td>approx. 0.5 - 1 m² / spray can</td></tr></table>	Colour:	light grey	Density:	approx. 0.8 g/cm ³	Drying:	dust-dry after approx. 30 minutes touch-dry after approx. 50 minutes polishable after approx. 2 - 4 hours	Coverage:	approx. 0.5 - 1 m ² / spray can
Colour:	light grey								
Density:	approx. 0.8 g/cm ³								
Drying:	dust-dry after approx. 30 minutes touch-dry after approx. 50 minutes polishable after approx. 2 - 4 hours								
Coverage:	approx. 0.5 - 1 m ² / spray can								

TDS 09.25

Technical Data Sheet

Page 2 of 2

- Storage:** If stored in dry and cool condition (5-25°C/41-77°F) in its closed original container at least 5 years from production.
- Health & Safety:** Read Safety Data Sheet before handling or using this product.
- Important Notice:** The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trials of the product, in an inconspicuous area or fabrication of a sample piece.