

Technical Data Sheet

Page 1 of 2

Properties:	<p>AKEMI® Thinner/Cleaner P is a product based on low boiling carboxylic acid esters.</p> <p>The product is characterized by the following qualities:</p> <ul style="list-style-type: none">- very high coverage if used as a thinner- very high cleaning and degreasing effect- very short evaporation time- evaporates without residue- free of reclaims- free of methanol, chlorinated hydrocarbons and paraffinic components
Application Area:	<p>AKEMI® Thinner/Cleaner P is used to dilute AKEMI® Polyester Spray Filler (max. addition 5%). Furthermore, due to its composition the product is best suited to remove fresh sealants, 1-component paints, residues of impregnations as well as grease, oil, wax etc. It can also be used as a degreasing agent for stone surfaces, such as granite, limestone, ceramics etc. which have to be bonded afterwards.</p>
Instructions for Use:	<ol style="list-style-type: none">1. Use as a thinner for AKEMI® Polyester Spray Filler:<ol style="list-style-type: none">a) Add maximum 5% of AKEMI® Thinner/Cleaner P.b) Stir the mixture homogenously, then pour into the spray gun and start working.2. Use as a cleaner:<ol style="list-style-type: none">a) Pour undiluted onto the surface and spread or apply with a cloth, a brush or a suitable pad.b) Let the product work for a short period of time and wipe off with a clean and lint-free cloth before the cleaner has evaporated.
Special Notes:	<ul style="list-style-type: none">- For professional use only.- Not suitable for plastics and paints which are sensitive to solvents. Test the compatibility on an inconspicuous area before use.- Only use on cold surface. Warm surfaces extremely accelerate the evaporation of the solvent and thus reduce the cleaning effect.- For proper waste disposal the container must be completely emptied.- Recycling in accordance with the guidelines of EU Decision 97/129 EC on the Packaging Directive 94/62/EC.
Technical Data:	<p>Colour: colourless, clear Density: 0.9 g/cm³</p>
Storage:	<p>If stored in dry and cool condition (5-25°C/41-77°F) in its closed original container at least 36 months from production.</p>
Health & Safety:	<p>Read Safety Data Sheet before handling or using this product.</p>

TDS 06.25

Technical Data Sheet

Page 2 of 2

Important Notice:

The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trials of the product, in an inconspicuous area or fabrication of a sample piece.