

# Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.11.2025

Version number 11 (replaces version 10)

Revision: 17.11.2025

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name: **Acrylic Thinner fast**

Article number: 70039, 70040

UFI: 2RE0-506K-A00H-P8QF

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Thinner, Diluent

### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH  
Lechstrasse 28  
D 90451 Nürnberg

Tel. +49(0)911-642960  
Fax. +49(0)911-644456  
e-mail info@akemi.de

Further information obtainable from:

Laboratory

### 1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH  
Tel. +49(0)911-64296-59  
Reachable during the following office hours:  
Monday – Thursday from 07:30 a.m. to 16:30 p.m.  
Friday from 07:30 a.m. to 13:30 p.m.

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS02 GHS07 GHS08

Signal word

Danger

Hazard-determining components of labelling:

reaction mass of ethylbenzole and xylene  
n-butyl acetate  
ethyl acetate

Hazard statements

H225 Highly flammable liquid and vapour.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H304 May be fatal if swallowed and enters airways.

(Contd. on page 2)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.11.2025

Version number 11 (replaces version 10)

Revision: 17.11.2025

**Trade name: Acrylic Thinner fast**

(Contd. of page 1)

· <u>Precautionary statements</u>	P101	If medical advice is needed, have product container or label at hand.
	P102	Keep out of reach of children.
	P103	Read carefully and follow all instructions.
	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P243	Take action to prevent static discharges.
	P260	Do not breathe vapours.
	P271	Use only outdoors or in a well-ventilated area.
	P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
	P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
	P331	Do NOT induce vomiting.
	P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
	P304+P312	IF INHALED: Call a POISON CENTER/doctor if you feel unwell.
	P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P403+P233	Store in a well-ventilated place. Keep container tightly closed.
	P405	Store locked up.
	P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

**· 2.3 Other hazards****· Results of PBT and vPvB assessment**

· PBT: Not applicable.

· vPvB: Not applicable.

**· Determination of endocrine-disrupting properties**

For information on endocrine disrupting properties see section 11.

**SECTION 3: Composition/information on ingredients****· 3.2 Mixtures**· Description: Mixture: consisting of the following components.**· Dangerous components:**

CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29	n-butyl acetate Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	25-50%
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46	ethyl acetate Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	25-50%
EC number: 905-588-0 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32 01-2119486136-34	reaction mass of ethylbenzole and xylene Flam. Liq. 3, H226 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 Aquatic Chronic 3, H412	12.5-25%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226 STOT SE 3, H336	<10%

(Contd. on page 3)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.11.2025

Version number 11 (replaces version 10)

Revision: 17.11.2025

**Trade name:** Acrylic Thinner fast

(Contd. of page 2)

· Additional information: For the wording of the listed hazard phrases refer to section 16.**SECTION 4: First aid measures****4.1 Description of first aid measures**

- General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.  
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately. Do not induce vomiting; call for medical help immediately.  
A person vomiting while laying on their back should be turned onto their side.

**4.2 Most important symptoms and effects, both acute and delayed**

Breathing difficulty  
Dizziness  
Headache

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

- Suitable extinguishing agents: CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet

**5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

**5.3 Advice for firefighters**

- Protective equipment: Wear fully protective suit.  
Mount respiratory protective device.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Keep away from ignition sources.  
Ensure adequate ventilation  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.

**6.2 Environmental precautions:**

Do not allow to penetrate the ground/soil.  
Prevent seepage into sewage system, workpits and cellars.  
Do not allow to enter sewers/ surface or ground water.

**6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

**6.4 Reference to other sections**

See Section 7 for information on safe handling.

(Contd. on page 4)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.11.2025

Version number 11 (replaces version 10)

Revision: 17.11.2025

**Trade name:** Acrylic Thinner fast

(Contd. of page 3)

See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

Keep away from heat and direct sunlight.  
Take note of emission threshold.  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.

**Information about fire - and explosion protection:**

Fumes can combine with air to form an explosive mixture.  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.

**7.2 Conditions for safe storage, including any incompatibilities****Storage:****Requirements to be met by storerooms and receptacles:**

Store only in the original receptacle.  
Store in a cool location.

**Information about storage in one common storage facility:**

Store away from oxidising agents.

**Further information about storage conditions:**

Protect from frost.  
Keep container tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.

**Storage class:**

3

**7.3 Specific end use(s)**

No further relevant information available.

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Ingredients with limit values that require monitoring at the workplace:****123-86-4 n-butyl acetate**

IOELV	Short-term value: 723 mg/m <sup>3</sup> , 150 ppm Long-term value: 241 mg/m <sup>3</sup> , 50 ppm
-------	--

**141-78-6 ethyl acetate**

IOELV	Short-term value: 1468 mg/m <sup>3</sup> , 400 ppm Long-term value: 734 mg/m <sup>3</sup> , 200 ppm
-------	--

**reaction mass of ethylbenzole and xylene**

AGW	Short-term value: 442 mg/m <sup>3</sup> , 100 ppm Long-term value: 221 mg/m <sup>3</sup> , 50 ppm H
-----	---

**108-65-6 2-methoxy-1-methylethyl acetate**

IOELV	Short-term value: 550 mg/m <sup>3</sup> , 100 ppm Long-term value: 275 mg/m <sup>3</sup> , 50 ppm Skin
-------	--

**DNELs****123-86-4 n-butyl acetate**

Oral	DNEL (Kurzzeit-akut)	2 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	2 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	11 mg/kg bw/day (ARB)

(Contd. on page 5)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.11.2025

Version number 11 (replaces version 10)

Revision: 17.11.2025

**Trade name: Acrylic Thinner fast**

(Contd. of page 4)

Inhalative	DNEL ( Langzeit-wiederholt)	6 mg/kg bw/day (BEV) 11 mg/kg bw/day (ARB)
	DNEL ( Kurzzeit-akut)	6 mg/kg bw/day (BEV) 600 mg/m <sup>3</sup> Air (ARB)
	DNEL ( Langzeit-wiederholt)	300 mg/m <sup>3</sup> Air (BEV)
		300 mg/m <sup>3</sup> Air (ARB) 35.7 mg/m <sup>3</sup> Air (BEV)

**141-78-6 ethyl acetate**

Oral	DNEL ( Langzeit-wiederholt)	4.5 mg/kg bw/day (BEV)
Dermal	DNEL ( Langzeit-wiederholt)	63 mg/kg bw/day (ARB)
		37 mg/kg bw/day (BEV)
Inhalative	DNEL ( Kurzzeit-akut)	1,468 mg/m <sup>3</sup> Air (ARB)
	DNEL ( Langzeit-wiederholt)	734 mg/m <sup>3</sup> Air (BEV)
		734 mg/m <sup>3</sup> Air (ARB) 367 mg/m <sup>3</sup> Air (BEV)

**reaction mass of ethylbenzole and xylene**

Oral	DNEL ( Langzeit-wiederholt)	1.6 mg/kg bw/day (BEV)
Dermal	DNEL ( Langzeit-wiederholt)	180 mg/kg bw/day (ARB)
		108 mg/kg bw/day (BEV)
Inhalative	DNEL ( Kurzzeit-akut)	289 mg/m <sup>3</sup> Air (ARB)
	DNEL ( Langzeit-wiederholt)	174 mg/m <sup>3</sup> Air (BEV)
		77-221 mg/m <sup>3</sup> Air (ARB) 14.8-174 mg/m <sup>3</sup> Air (BEV)

**108-65-6 2-methoxy-1-methylethyl acetate**

Oral	DNEL ( Kurzzeit-akut)	500 mg/kg bw/day (BEV)
Dermal	DNEL ( Langzeit-wiederholt)	1.67 mg/kg bw/day (BEV)
	DNEL ( Langzeit-wiederholt)	796 mg/kg bw/day (ARB)
Inhalative	DNEL ( Kurzzeit-akut)	54.8 mg/kg bw/day (BEV)
		550 mg/m <sup>3</sup> Air (ARB)
	DNEL ( Langzeit-wiederholt)	33 mg/m <sup>3</sup> Air (BEV) 275 mg/m <sup>3</sup> Air (ARB) 33 mg/m <sup>3</sup> Air (BEV)

## · PNECs

**123-86-4 n-butyl acetate**

PNEC (wässrig)	35.6 mg/l (KA)
	0.018 mg/l (MW)
	0.18 mg/l (SW)
	0.36 mg/l (WAS)
PNEC (fest)	0.0903 mg/kg Trockengew (BO)
	0.0981 mg/kg Trockengew (MWS)
	0.981 mg/kg Trockengew (SWS)

**141-78-6 ethyl acetate**

PNEC (wässrig)	650 mg/l (KA)
	0.024 mg/l (MW)
	0.24 mg/l (SW)

(Contd. on page 6)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.11.2025

Version number 11 (replaces version 10)

Revision: 17.11.2025

**Trade name: Acrylic Thinner fast**

(Contd. of page 5)

PNEC (fest)	1.65 mg/l (WAS) 0.148 mg/kg Trockengew (BO) 0.115 mg/kg Trockengew (MWS) 1.15 mg/kg Trockengew (SWS)
<b>reaction mass of ethylbenzole and xylene</b>	
PNEC (wässrig)	1.6 mg/l (KA) 0.004 mg/l (MW) 0.044 mg/l (SW) 0.01 mg/l (WAS)
PNEC (fest)	0.852 mg/kg Trockengew (BO) 0.252 mg/kg Trockengew (MWS) 2.52 mg/kg Trockengew (SWS)
<b>108-65-6 2-methoxy-1-methylethyl acetate</b>	
PNEC (wässrig)	100 mg/l (KA) 0.0635 mg/l (MW) 0.635 mg/l (SW) 6.35 mg/l (WAS)
PNEC (fest)	0.29 mg/kg Trockengew (BO) 0.329 mg/kg Trockengew (MWS) 3.29 mg/kg Trockengew (SWS)

· Additional information: The lists valid during the making were used as basis.

· **8.2 Exposure controls**

- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Do not eat, drink, smoke or sniff while working.

Use skin protection cream for skin protection.

Clean skin thoroughly immediately after handling the product.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· Respiratory protection:

Filter AX

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH,

(Contd. on page 7)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.11.2025

Version number 11 (replaces version 10)

Revision: 17.11.2025

**Trade name:** Acrylic Thinner fast

(Contd. of page 6)

Germany, 36124 Eichenzell, internet: <http://www.kcl.de>.**Protective gloves**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Nitrile rubber, NBR

Neoprene gloves

PVA gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove materialValue for the permeation: Level  $\leq 1$ , 30 min

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are suitable:

Butyl rubber, BR

· As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

Butoject (KCL, Art\_No. 897, 898)

Butyl rubber, BR

· Not suitable are gloves made of the following materials:

Leather gloves

Strong material gloves

Nitrile rubber, NBR

· Eye/face protection**Tightly sealed goggles**· Body protection:

Solvent resistant protective clothing

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**· General Information· Colour:

Colourless

· Odour:

Specific type

· Odour threshold:

Not determined.

· Melting point/freezing point:

Undetermined.

Not applicable

· Boiling point or initial boiling point and boiling range

76-78 °C

· Flammability

Not applicable.

· Lower and upper explosion limit· Lower:

2.1 Vol %

· Upper:

11.5 Vol %

· Flash point:

-4 °C

· Auto-ignition temperature:

315 °C

(Contd. on page 8)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.11.2025

Version number 11 (replaces version 10)

Revision: 17.11.2025

**Trade name: Acrylic Thinner fast**

(Contd. of page 7)

· <u>Decomposition temperature:</u>	Not determined.
· <u>pH</u>	Not determined.
	Not applicable
· <u>Viscosity:</u>	
· <u>Kinematic viscosity</u>	Not determined.
· <u>Dynamic:</u>	Not determined.
· <u>Solubility</u>	
· <u>water:</u>	Not miscible or difficult to mix.
· <u>Partition coefficient n-octanol/water (log value)</u>	Not determined.
· <u>Vapour pressure at 20 °C:</u>	97 hPa
· <u>Vapour pressure at 50 °C:</u>	360 hPa
· <u>Density and/or relative density</u>	
· <u>Density at 20 °C:</u>	0.89 g/cm <sup>3</sup>
· <u>Relative density</u>	Not determined.
· <u>Vapour density</u>	Not determined.

**9.2 Other information**

· <u>Appearance:</u>	
· <u>Form:</u>	Liquid
· <u>Important information on protection of health and environment, and on safety.</u>	
· <u>Ignition temperature:</u>	Product is not selfigniting.
· <u>Explosive properties:</u>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <u>Solvent content:</u>	
· <u>Organic solvents:</u>	100.0 %
· <u>Solids content:</u>	0.0 %
· <u>Change in condition</u>	
· <u>Evaporation rate</u>	Not determined.

· <u>Information with regard to physical hazard classes</u>	
· <u>Explosives</u>	Void
· <u>Flammable gases</u>	Void
· <u>Aerosols</u>	Void
· <u>Oxidising gases</u>	Void
· <u>Gases under pressure</u>	Void
· <u>Flammable liquids</u>	Highly flammable liquid and vapour.
· <u>Flammable solids</u>	Void
· <u>Self-reactive substances and mixtures</u>	Void
· <u>Pyrophoric liquids</u>	Void
· <u>Pyrophoric solids</u>	Void
· <u>Self-heating substances and mixtures</u>	Void
· <u>Substances and mixtures, which emit flammable gases in contact with water</u>	Void
· <u>Oxidising liquids</u>	Void
· <u>Oxidising solids</u>	Void
· <u>Organic peroxides</u>	Void
· <u>Corrosive to metals</u>	Void
· <u>Desensitised explosives</u>	Void

**SECTION 10: Stability and reactivity**

· <b>10.1 Reactivity</b>	No further relevant information available.
· <b>10.2 Chemical stability</b>	
· <u>Thermal decomposition / conditions to be avoided:</u>	No decomposition if used according to specifications.

(Contd. on page 9)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.11.2025

Version number 11 (replaces version 10)

Revision: 17.11.2025

**Trade name:** Acrylic Thinner fast

(Contd. of page 8)

· **10.3 Possibility of hazardous reactions**

Reacts with acids, alkalis and oxidising agents.  
Reacts with strong oxidising agents.  
Flammable vapour-air mixtures may develop if stored in large receptacles and above room temperature.

· **10.4 Conditions to avoid**

No further relevant information available.

· **10.5 Incompatible materials:**

No further relevant information available.

· **10.6 Hazardous decomposition products:**

Carbon monoxide and carbon dioxide  
Nitrogen oxides (NOx)  
Possible in traces.

\* **SECTION 11: Toxicological information**

· **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

**ATE (Acute Toxicity Estimates)**

Dermal	ATE mix	5,500 mg/kg
Inhalative	LC50/4 h	55 mg/l (rat)

**123-86-4 n-butyl acetate**

Oral	LD50	10,760 mg/kg (rat) (OECD 423)
Dermal	LD50	14,112 mg/kg (rat) (OECD 402)
Inhalative	LC50/4 h	>21 mg/l (rat) (OECD 403)
	LC50	390 mg/m <sup>3</sup> (rat)
	LC50/48h	64 mg/l (Brachydanio rerio)

**141-78-6 ethyl acetate**

Oral	LD50	4,100 mg/kg (mouse)	
		5,620 mg/kg (rat)	
		4,934 mg/kg (rabbit) (OECD 401)	
Dermal	NOAEL-Werte	900 mg/kg (rat)	
		>18,000 mg/kg (rabbit) (OECD 402)	
Inhalative	LC50	58 mg/l (rat)	
		LC50/4 h	56 mg/l (rat)
		LC50/1h	200 mg/l (rat)
		LC50/8h	5.86 mg/l (rat)
		LC50/48h	333 mg/l (Leuciscus idus)

**reaction mass of ethylbenzole and xylene**

Oral	LD50	3,523 mg/kg (rat)
		NOAEL-Werte
Dermal	LD50	12,126 mg/kg (rabbit)
		ATE mix
Inhalative	LC50/4h	29,000 mg/m <sup>3</sup> (rat)
		LC50/4 h

**108-65-6 2-methoxy-1-methylethyl acetate**

Oral	LD50	8,500 mg/kg (rat) (OECD 401)
		NOAEL-Werte

(Contd. on page 10)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.11.2025

Version number 11 (replaces version 10)

Revision: 17.11.2025

**Trade name: Acrylic Thinner fast**

(Contd. of page 9)

Dermal	LD50	>5,000 mg/kg (rabbit) (OECD 402)
		>2,000 mg/kg (rat)
Inhalative	LC50/4h	>10,000 mg/m <sup>3</sup> (rat)
	LC50	>23.8 mg/l (rat)
	LC50/4 h	35.7 mg/l (rat)
	LC50/48h	100 mg/l (Desmodesmus subspicatus)

- Primary irritant effect: Do not get in eyes, on skin, or on clothing.
- Skin corrosion/irritation Causes skin irritation.
- Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

- Endocrine disrupting properties

None of the ingredients is listed.

**SECTION 12: Ecological information**· **12.1 Toxicity**

- Aquatic toxicity:

**123-86-4 n-butyl acetate**

EC50/24h	72.8 mg/l (daphnia magna) (DIN 38412)
EC50/96h	320 mg/l (algae)
LC50/24h	205 mg/l (daphnia magna)
IC50/72h	648 mg/l (Desmodesmus subspicatus)
EC10/18h	959 mg/l (pseudomonas putida)
EC50/48h	44 mg/l (daphnia magna) (OECD 202)
ErC50/72h	675 mg/l (Scenedesmus subspicatus)
EC50/16h	959 mg/l (pseudomonas putida)
NOEC	200 mg/kg (Desmodesmus subspicatus)
NOEC/21d	23 mg/l (daphnia magna) (OECD 211)
EC50/72h	647.7 mg/l (Desmodesmus subspicatus) (Zellvermehrungshemmtest)
	397 mg/l (Scenedesmus subspicatus)
LC50/96h	62 mg/l (Danio rerio.)
	81 mg/l (piscis)
	100 mg/l (Iepomis macrochirus)
	62 mg/l (Leuciscus idus) (DIN 38412)
	mg/l (Oncorhynchus mykiss)
	18 mg/l (Pimephales promelas) (OECD 203)

**141-78-6 ethyl acetate**

EC50/24h	2,300-3,090 mg/l (daphnia magna)
EC50/96h	220 mg/l (Pimephales promelas)
EC10/18h	2,900 mg/l (pseudomonas putida)

(Contd. on page 11)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.11.2025

Version number 11 (replaces version 10)

Revision: 17.11.2025

**Trade name: Acrylic Thinner fast**

(Contd. of page 10)

EC50/48h	610 mg/l (daphnia magna) (DIN 38412)
	5,600 mg/l (Scenedesmus subspicatus)
IC50/48h	3,300 mg/l (Scenedesmus subspicatus)
LC 0	29.3 mg/l (rat)
NOELR/72h	>100 mg/l (Desmodium subspicatus) (OECD 201)
NOEC/21d	2.4 mg/l (daphnia magna) (DIN 38412 Part 11)
EC10	2,900 mg/l (pseudomonas putida)
EC50/48h	3,300 mg/l (Scenedesmus subspicatus)
EC50/72h	1,800-3,200 mg/l (senastrum capricornutum)
LC50/96h	300-600 mg/l (Oncorhynchus mykiss)
	230 mg/l (Pimephales promelas)

**reaction mass of ethylbenzole and xylene**

LC50/24h	1 mg/l (daphnia magna) (OECD 202)
EC50/48h	3.2-9.5 mg/l (daphnia magna) (US EPA)
ErC50/72h	4.9 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
NOEC	16 mg/l (BES)
	1.3 mg/l (Oncorhynchus mykiss)
NOELR/72h	0.44 mg/l (Pseudokirchneriella subcapitata)
NOEC/21d	1.57 mg/l (daphnia magna) (OECD 211)
NOELR/28d	16 mg/l (bacteria)
EC50/72h	1-10 mg/l (algae)
	4.7 mg/l (senastrum capricornutum) (OECD 201)
LC50/96h	1-10 mg/l (fish)
	86 mg/l (Leuciscus idus)
	2.6 mg/l (Oncorhynchus mykiss) (OECD 203)
	8.9-16.4 mg/l (pimephales promelas)

**108-65-6 2-methoxy-1-methylethyl acetate**

EC50	>500 mg/l (daphnia magna)
LC50	>100 mg/l (Oryzias latipes)
EC50/48h	>500 mg/l (daphnia magna) (RL 67/548/EWG. Anhang V, C.2.)
ErC50/72h	>1,000 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
EC20/0.5h	>1,000 mg/l (BES) (OECD 209)
NOEC	47.5 mg/l (Oryzias latipes)
NOEC/21d	≥100 mg/l (daphnia magna)
EC10	>1,000 mg/l (BES)
EC50/72h	>1,000 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	100-180 mg/l (Oncorhynchus mykiss)
	>100 mg/l (Oryzias latipes)
	161 mg/l (Pimephales promelas)

- **12.2 Persistence and degradability**

No further relevant information available.

- **12.3 Bioaccumulative potential**

No further relevant information available.

- **12.4 Mobility in soil**

No further relevant information available.

- **12.5 Results of PBT and vPvB assessment**

- **PBT:**

Not applicable.

- **vPvB:**

Not applicable.

(Contd. on page 12)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.11.2025

Version number 11 (replaces version 10)

Revision: 17.11.2025

**Trade name:** Acrylic Thinner fast

(Contd. of page 11)

· **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

· **12.7 Other adverse effects**

· Additional ecological information:

· General notes:

Do not allow product to reach ground water, water course or sewage system.  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

### SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

07 00 00	WASTES FROM ORGANIC CHEMICAL PROCESSES
----------	--

07 01 00	wastes from the manufacture, formulation, supply and use (MFSU) of basic organic chemicals
----------	--

07 01 04*	other organic solvents, washing liquids and mother liquors
-----------	--

· Uncleaned packaging:

· Recommendation:

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

### SECTION 14: Transport information

· **14.1 UN number or ID number**

· ADR, IMDG, IATA

UN1993

· **14.2 UN proper shipping name**

· ADR

1993 FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE, BUTYL ACETATES), special provision 640C

· IMDG, IATA

FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE, BUTYL ACETATES)

· **14.3 Transport hazard class(es)**

· ADR



· Class

3 (F1) Flammable liquids.

· Label

3

· IMDG, IATA



· Class

3 Flammable liquids.

· Label

3

· **14.4 Packing group**

· ADR, IMDG, IATA

II

(Contd. on page 13)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.11.2025

Version number 11 (replaces version 10)

Revision: 17.11.2025

**Trade name:** Acrylic Thinner fast

(Contd. of page 12)

**14.5 Environmental hazards:**

· Marine pollutant: No

**14.6 Special precautions for user**

Warning: Flammable liquids.

· Hazard identification number (Kemler code): 33

· EMS Number: F-E, S-E

· Stowage Category: B

**14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

## · Transport/Additional information:

## · ADR

· Limited quantities (LQ) 1L

· Excepted quantities (EQ) Code: E2  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 500 ml

· Transport category 2

· Tunnel restriction code D/E

## · IMDG

· Limited quantities (LQ) 1L

· Excepted quantities (EQ) Code: E2  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 500 ml

## · UN "Model Regulation":

UN 1993 FLAMMABLE LIQUID, N.O.S. (ETHYL ACETATE, BUTYL ACETATES), 3, II

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

(Contd. on page 14)

EU

## Safety data sheet

### according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.11.2025

Version number 11 (replaces version 10)

Revision: 17.11.2025

**Trade name: Acrylic Thinner fast**

(Contd. of page 13)

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· National regulations:

· Information about limitation of use: Employment restrictions concerning pregnant and lactating women must be observed.  
Employment restrictions concerning juveniles must be observed.

· Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· VOC EU 889.6 g/l· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

· Department issuing SDS: Laboratory· Date of previous version: 05.11.2024· Version number of previous version: 10

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)  
ICAO: International Civil Aviation Organisation  
ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)  
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
DNEL: Derived No-Effect Level (REACH)  
PNEC: Predicted No-Effect Concentration (REACH)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
SVHC: Substances of Very High Concern  
vPvB: very Persistent and very Bioaccumulative  
ATE: Acute toxicity estimate values  
Flam. Liq. 2: Flammable liquids – Category 2  
Flam. Liq. 3: Flammable liquids – Category 3  
Acute Tox. 4: Acute toxicity – Category 4  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2  
Asp. Tox. 1: Aspiration hazard – Category 1  
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

EU