

Technical Data Sheet

Page 1 of 2

- Properties:** AKEMI® Acryclean is a highly pure solvent for residue-free cleaning of various surfaces.
- The product features and benefits are as following:
- removes even stubborn silicone deposits
 - designed to leave a perfectly clean and contamination-free surface
 - evaporates without residues
 - removes adhesive residues without leaving residues
- Application Area:**
- for cleaning and degreasing of surfaces before bonding, sealing or coating on non-absorbent surfaces (e.g. ceramics, metals etc.)
 - for the removal of grease, oil and silicone contamination, waxes, tar deposits, tree resin, sealant and adhesive residues
 - for the removal of stickers, foils and tapes
 - for smoothing and removal of sealants
 - also suitable for natural stone and many artificial stones
- Instructions for use:**
- Cleaning and degreasing before bonding or coating applications:**
1. Spray AKEMI® Acryclean on the surface or apply with a cloth.
 2. Thoroughly wipe dry with a clean cloth.
 3. Allow to flash off for 5 to 10 minutes before bonding or coating.
- Removal of adhesives or sealants:**
1. Remove residues of adhesives or sealants mechanically as far as possible.
 2. Wet residues thoroughly with AKEMI® Acryclean.
 3. Allow to work for 5 to 10 minutes.
 4. Remove residues with a cloth or a brush.
- Removal of adhesives:**
1. Wet the adhesive residues thoroughly with AKEMI® Acryclean.
 2. Allow to work for 2 to 10 minutes.
 3. Remove the loosened residues.
- Special Notes:**
- For professional use only.
 - Not suitable for all plastic or painted surfaces. Test compatibility on an inconspicuous area before use.
 - For proper waste disposal, the container must be completely emptied.
 - Recycling in accordance with the guidelines of EU Decision 97/129 EC on the Packaging Directive 94/62/EC.
- Technical Data:**
- | | |
|------------------------|--|
| Base: | mixture of aliphatic and aromatic hydrocarbons |
| Colour: | colourless |
| Odour: | strong white spirit |
| Working temperature: | +10°C to +35°C |
| Density: | 0.75 g/ml / 20°C (spray can)
0.80 g/ml / 20°C (can, canister, drum) |
| VOC | |
| ○ spray can: | 746 g/l |
| ○ can, canister, drum: | 796 g/l |
- Storage:** If stored in dry and cool condition (5 - 25°C/41 - 77°F) in its closed original container at least 24 months from production.

TDS 03.25

Technical Data Sheet

Page 2 of 2

- Health & Safety:** Read Safety Data Sheet before handling or using this product.
- Important Notice:** The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information - as well as other oral or written technical advises - must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trials of the product, in an inconspicuous area or fabrication of a sample piece.

TDS 03.25