

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.11.2024

Version number 7 (replaces version 6)

Revision: 19.11.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Spray Transparent Grease 3**

Article number: 88557

UFI: AJGJ-A6FC-Y78Q-0AD1

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Grease

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH
Lechstrasse 28
D 90451 Nürnberg

Tel. +49(0)911-642960
Fax. +49(0)911-644456
e-mail info@akemi.de

Further information obtainable from:

Laboratory

1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH
Tel. +49(0)911-64296-59
Reachable during the following office hours:
Monday – Thursday from 07:30 a.m. to 16:30 p.m.
Friday from 07:30 a.m. to 13:30 p.m.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

Response: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Storage:

Store in a well-ventilated place. Keep cool.

Store in a well-ventilated place. Keep container tightly closed.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS02 GHS07 GHS09

Signal word

Danger

Hazard-determining components of labelling:

Kohlenwasserstoffe, C7, n-Alkane, Isoalkane, Cycloalkane
calcium dihydroxide

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, < 5% n-hexane

(Contd. on page 2)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.11.2024

Version number 7 (replaces version 6)

Revision: 19.11.2024

Trade name: Spray Transparent Grease 3

(Contd. of page 1)

· <u>Hazard statements</u>	H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
	H315 Causes skin irritation.
	H319 Causes serious eye irritation.
	H336 May cause drowsiness or dizziness.
	H411 Toxic to aquatic life with long lasting effects.
· <u>Precautionary statements</u>	P101 If medical advice is needed, have product container or label at hand.
	P102 Keep out of reach of children.
	P103 Read carefully and follow all instructions.
	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P211 Do not spray on an open flame or other ignition source.
	P251 Do not pierce or burn, even after use.
	P260 Do not breathe spray.
	P271 Use only outdoors or in a well-ventilated area.
	P273 Avoid release to the environment.
	P280 Wear protective gloves / eye protection.
	P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
	P331 Do NOT induce vomiting.
	P302+P352 IF ON SKIN: Wash with plenty of water.
	P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P403+P233 Store in a well-ventilated place. Keep container tightly closed.
	P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
	P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
· 2.3 Other hazards	The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds or formaldehydes.
· <u>Results of PBT and vPvB assessment</u>	
· <u>PBT:</u>	Not applicable.
· <u>vPvB:</u>	Not applicable.
· <u>Determination of endocrine-disrupting properties</u>	For information on endocrine disrupting properties see section 11.

SECTION 3: Composition/information on ingredients**3.2 Mixtures**· Description: Mixture: consisting of the following components.· Dangerous components:

CAS: 64742-49-0 EC number: 927-510-4 Reg.nr.: 01-2119475515-33	Kohlenwasserstoffe, C7, n-Alkane, Isoalkane, Cycloalkane Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H336 EUH066	25-50%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane, pure Flam. Gas 1A, H220 Press. Gas (Comp.), H280	25-50%

(Contd. on page 3)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.11.2024

Version number 7 (replaces version 6)

Revision: 19.11.2024

Trade name: Spray Transparent Grease 3

(Contd. of page 2)

CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	<12.5%
CAS: 92128-66-0 EC number: 921-024-6 Reg.nr.: 01-2119475514-35	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, < 5% n-hexane Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H336	<10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-01-8 Reg.nr.: 01-2119485395-27	isobutane (containing $\geq 0,1\%$ butadiene (203-450-8)) Flam. Gas 1A, H220; Flam. Liq. 1, H224 Press. Gas (Comp.), H280	1-5%
CAS: 1305-62-0 EINECS: 215-137-3 Reg.nr.: 01-2119475151-45	calcium dihydroxide Eye Dam. 1, H318 Skin Irrit. 2, H315; STOT SE 3, H335	1-5%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures**

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

Headache
Dizziness
Dizziness

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

- Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:
Carbon monoxide (CO)
Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

- Protective equipment: Mount respiratory protective device.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.11.2024

Version number 7 (replaces version 6)

Revision: 19.11.2024

Trade name: Spray Transparent Grease 3

(Contd. of page 3)

- **6.2 Environmental precautions:** Do not allow to penetrate the ground/soil.
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections** See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- **Information about fire - and explosion protection:** Fumes can combine with air to form an explosive mixture.
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Protect from frost.
Keep container tightly sealed.
Do not seal receptacle gas tight.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **Storage class:** 2 B
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

1305-62-0 calcium dihydroxide

IOELV	Short-term value: 4 mg/m ³ Long-term value: 1 mg/m ³ Respirable fraction
-------	--

- **DNELs**

64742-49-0 Kohlenwasserstoffe, C7, n-Alkane, Isoalkane, Cycloalkane

Oral	DNEL (Langzeit-wiederholt)	149 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	300 mg/kg bw/day (ARB)

(Contd. on page 5)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.11.2024

Version number 7 (replaces version 6)

Revision: 19.11.2024

Trade name: Spray Transparent Grease 3

(Contd. of page 4)

Inhalative	DNEL (Langzeit-wiederholt)	149 mg/kg bw/day (BEV) 2,085 mg/m ³ Air (ARB) 477 mg/m ³ Air (BEV)
92128-66-0 Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, < 5% n-hexane		
Oral	DNEL (Langzeit-wiederholt)	699 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	773 mg/kg bw/day (ARB) 699 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	2,035 mg/m ³ Air (ARB) 608 mg/m ³ Air (BEV)
1305-62-0 calcium dihydroxide		
Inhalative	DNEL (Kurzzeit-akut)	4 mg/m ³ Air (ARB) 4 mg/m ³ Air (BEV)
	DNEL (Langzeit-wiederholt)	1 mg/m ³ Air (ARB) 1 mg/m ³ Air (BEV)

· Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.
Use skin protection cream for skin protection.
Clean skin thoroughly immediately after handling the product.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

- Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Short term filter device:
Filter AX
- Hand protection Preventive skin protection by use of skin-protecting agents is recommended.
After use of gloves apply skin-cleaning agents and skin cosmetics.

**Protective gloves**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type.
The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.
This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with

(Contd. on page 6)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.11.2024


Version number 7 (replaces version 6)

Revision: 19.11.2024

Trade name: Spray Transparent Grease 3

(Contd. of page 5)

different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).

- Material of gloves Fluorocarbon rubber (Viton)
Nitrile rubber, NBR
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- Penetration time of glove material Value for the permeation: Level ≤ 6, 480 min
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)
Vitoject (KCL, Art_No. 890)
Butyl rubber, BR
- As protection from splashes gloves made of the following materials are suitable: Nitrile rubber, NBR
Camatril (KCL, 730, 731, 732, 733)
Butoject (KCL, Art_No. 897, 898)
Butyl rubber, BR
- Not suitable are gloves made of the following materials: Leather gloves
Strong material gloves
- Eye/face protection  Tightly sealed goggles
- Body protection: Use protective suit.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

- General Information
- Colour: According to product specification
- Odour: Specific type
- Odour threshold: Not determined.
- Melting point/freezing point: Undetermined.
- Boiling point or initial boiling point and boiling range -44 °C
- Flammability Not applicable.
- Lower and upper explosion limit
- Lower: 1.5 Vol % (106-97-8 butane, pure)
- Upper: 10.9 Vol % (74-98-6 propane)
- Flash point: -97 °C
- Auto-ignition temperature: 365 °C
- Decomposition temperature: Not determined.
- pH Not determined.
- Viscosity: Not applicable
- Kinematic viscosity Not determined.
- Dynamic: Not determined.

(Contd. on page 7)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.11.2024

Version number 7 (replaces version 6)

Revision: 19.11.2024

Trade name: Spray Transparent Grease 3

(Contd. of page 6)

· <u>Solubility</u>	
· <u>water:</u>	Not miscible or difficult to mix.
· <u>Partition coefficient n-octanol/water (log value)</u>	Not determined.
· <u>Vapour pressure at 20 °C:</u>	2,100 hPa
· <u>Density and/or relative density</u>	
· <u>Density at 20 °C:</u>	0.64 g/cm ³
· <u>Relative density</u>	Not determined.
· <u>Vapour density</u>	Not determined.

9.2 Other information

· <u>Appearance:</u>	
· <u>Form:</u>	Aerosol
· <u>Important information on protection of health and environment, and on safety.</u>	
· <u>Ignition temperature:</u>	Product is not selfigniting.
· <u>Explosive properties:</u>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <u>Solvent content:</u>	
· <u>Organic solvents:</u>	77.4 %
· <u>Solids content:</u>	15.7 %
· <u>Change in condition</u>	
· <u>Evaporation rate</u>	Not applicable.

Information with regard to physical hazard classes

· <u>Explosives</u>	Void
· <u>Flammable gases</u>	Void
· <u>Aerosols</u>	Extremely flammable aerosol. Pressurised container: May burst if heated.
· <u>Oxidising gases</u>	Void
· <u>Gases under pressure</u>	Void
· <u>Flammable liquids</u>	Void
· <u>Flammable solids</u>	Void
· <u>Self-reactive substances and mixtures</u>	Void
· <u>Pyrophoric liquids</u>	Void
· <u>Pyrophoric solids</u>	Void
· <u>Self-heating substances and mixtures</u>	Void
· <u>Substances and mixtures, which emit flammable gases in contact with water</u>	Void
· <u>Oxidising liquids</u>	Void
· <u>Oxidising solids</u>	Void
· <u>Organic peroxides</u>	Void
· <u>Corrosive to metals</u>	Void
· <u>Desensitised explosives</u>	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity	No further relevant information available.
· 10.2 Chemical stability	
· <u>Thermal decomposition / conditions to be avoided:</u>	No decomposition if used according to specifications.
· 10.3 Possibility of hazardous reactions	No dangerous reactions known.
· 10.4 Conditions to avoid	No further relevant information available.
· 10.5 Incompatible materials:	No further relevant information available.

(Contd. on page 8)

EU

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.11.2024

Version number 7 (replaces version 6)

Revision: 19.11.2024

Trade name: Spray Transparent Grease 3

(Contd. of page 7)

· **10.6 Hazardous decomposition products:**

No dangerous decomposition products known.

SECTION 11: Toxicological information

· **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

64742-49-0 Kohlenwasserstoffe, C7, n-Alkane, Isoalkane, Cycloalkane

Oral	LD50	>5,840 mg/kg (rat)
Dermal	LD50	2,800-3,100 mg/kg (rabbit)
		>2,920 mg/kg (rat)
Inhalative	LC50/4 h	>23.3 mg/l (rat)

106-97-8 butane, pure

Inhalative	LC50/4 h	658 mg/l (rat)
------------	----------	----------------

74-98-6 propane

Inhalative	LC50/4 h	>20 mg/l (rat)
------------	----------	----------------

92128-66-0 Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, < 5% n-hexane

Oral	LD50	>5,840 mg/kg (rat)
Dermal	LD50	>2,920 mg/kg (rabbit)
	LD50	>3,160 mg/kg (rabbit) (IUCLID)
		>2,920 mg/kg (rat)
Inhalative	LC50/4 h	>25.2 mg/l (rat) (IUCLID)

1305-62-0 calcium dihydroxide

Oral	LD50	>2,001 mg/kg (rat)
Dermal	LD50	>2,500 mg/kg (rabbit)

· Primary irritant effect:

· Skin corrosion/irritation Causes skin irritation.

· Serious eye damage/irritation Causes serious eye irritation.

· Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity Based on available data, the classification criteria are not met.

· Reproductive toxicity Based on available data, the classification criteria are not met.

· STOT-single exposure May cause drowsiness or dizziness.

· STOT-repeated exposure Based on available data, the classification criteria are not met.

· Aspiration hazard May be fatal if swallowed and enters airways.

· **11.2 Information on other hazards**

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· **12.1 Toxicity**

· Aquatic toxicity:

64742-49-0 Kohlenwasserstoffe, C7, n-Alkane, Isoalkane, Cycloalkane

LC50	35-37 mg/l (piscis)
EC50/48h	3 mg/l (daphnia magna)
EL50/72h	10-30 mg/l (algae)

(Contd. on page 9)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.11.2024

Version number 7 (replaces version 6)

Revision: 19.11.2024

Trade name: Spray Transparent Grease 3

(Contd. of page 8)

NOELR/72h	10 mg/l (Pseudokirchneriella subcapitata)
NOEC/21d	0.17 mg/l (daphnia magna)
EC50/72h	10-30 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	>13.4 mg/l (Oncorhynchus mykiss)

92128-66-0 Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclene, < 5% n-hexane

EC50/48h	3 mg/l (daphnia magna)
EL50/48h	3 mg/l (daphnia magna)
EL50/72h	30-100 mg/l (Pseudokirchneriella subcapitata)
LL50/96h	11.4 mg/l (Oncorhynchus mykiss)
NOELR/72h	3 mg/l (Pseudokirchneriella subcapitata)
NOEC/21d	0.17 mg/l (daphnia magna)
LC50/96h	2.6 mg/l (piscis) (IUCLID)
LC50/72h	15.8 mg/l (Oncorhynchus mykiss)

1305-62-0 calcium dihydroxide

EC50/96h	160 mg/l (piscis)
EC50	59.1 mg/l (daphnia magna)
EC50/72h	184.57 mg/l (algae)
LC50/96h	50.6 mg/l (piscis)

- **12.2 Persistence and degradability**

No further relevant information available.

- **12.3 Bioaccumulative potential**

No further relevant information available.

- **12.4 Mobility in soil**

No further relevant information available.

- **12.5 Results of PBT and vPvB assessment**

- PBT: Not applicable.

- vPvB: Not applicable.

- **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

- **12.7 Other adverse effects**

- Remark: Toxic for fish

- **Additional ecological information:**

- **General notes:**

Do not allow product to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**

- **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **Uncleaned packaging:**

- **Recommendation:**

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

Disposal must be made according to official regulations.

(Contd. on page 10)

EU

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.11.2024

Version number 7 (replaces version 6)

Revision: 19.11.2024

Trade name: Spray Transparent Grease 3

(Contd. of page 9)

SECTION 14: Transport information**· 14.1 UN number or ID number**· ADR, IMDG, IATA UN1950**· 14.2 UN proper shipping name**

· ADR 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS
 · IMDG AEROSOLS, MARINE POLLUTANT
 · IATA AEROSOLS, flammable

· 14.3 Transport hazard class(es)· ADR

· Class 2.5F Gases.
 · Label 2.1

· IMDG

· Class 2.1 Gases.
 · Label 2.1

· IATA

· Class 2.1 Gases.
 · Label 2.1

· 14.4 Packing group· ADR, IMDG, IATA Void**· 14.5 Environmental hazards:**

· Marine pollutant: Product contains environmentally hazardous substances:
 Yes
 Symbol (fish and tree)
 Symbol (fish and tree)

· Special marking (ADR):**· 14.6 Special precautions for user**

· Hazard identification number (Kemler code): Warning: Gases.
 -
 · EMS Number: F-D,S-U
 · Stowage Code SW1 Protected from sources of heat.
 SW22 For AEROSOLS with a maximum capacity of 1 litre:
 Category A. For AEROSOLS with a capacity above 1 litre:
 Category B. For WASTE AEROSOLS: Category C, Clear of
 living quarters.

(Contd. on page 11)

EU

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.11.2024

Version number 7 (replaces version 6)

Revision: 19.11.2024

Trade name: Spray Transparent Grease 3

(Contd. of page 10)

· <u>Segregation Code</u>	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· <u>Transport/Additional information:</u>	
· <u>ADR</u>	
· <u>Limited quantities (LQ)</u>	1L
· <u>Excepted quantities (EQ)</u>	Code: E0 Not permitted as Excepted Quantity
· <u>Transport category</u>	2
· <u>Tunnel restriction code</u>	D
· <u>IMDG</u>	
· <u>Limited quantities (LQ)</u>	1L
· <u>Excepted quantities (EQ)</u>	Code: E0 Not permitted as Excepted Quantity
· <u>UN "Model Regulation":</u>	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P3a FLAMMABLE AEROSOLS
E2 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

(Contd. on page 12)

EU

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 19.11.2024

Version number 7 (replaces version 6)

Revision: 19.11.2024

Trade name: Spray Transparent Grease 3

(Contd. of page 11)

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· National regulations:

- Information about limitation of use: Employment restrictions concerning pregnant and lactating women must be observed.
Employment restrictions concerning juveniles must be observed.

- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

- VOC EU 527.4 g/l

· 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

· Department issuing SDS: Laboratory

· Date of previous version: 26.01.2023

· Version number of previous version: 6

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern
vPvB: very Persistent and very Bioaccumulative
ATE: Acute toxicity estimate values
Flam. Gas 1A: Flammable gases – Category 1A
Aerosol 1: Aerosols – Category 1
Press. Gas (Comp.): Gases under pressure – Compressed gas
Flam. Liq. 1: Flammable liquids – Category 1
Flam. Liq. 2: Flammable liquids – Category 2
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2