

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 20.02.2024

Version number 12 (replaces version 11)

Revision: 20.02.2024

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name: **Zinc Spray**

Article number: 90213

UFI: KHSG-1Y58-HC87-KR5R

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

#### Application of the substance / the mixture

Spray varnish

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH  
Lechstrasse 28  
D 90451 Nürnberg

Tel. +49(0)911-642960  
Fax. +49(0)911-644456  
e-mail info@akemi.de

#### Further information obtainable from:

Laboratory

#### 1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH  
Tel. +49(0)911-64296-59  
Reachable during the following office hours:  
Monday – Thursday from 07:30 a.m. to 16:30 p.m.  
Friday from 07:30 a.m. to 13:30 p.m.

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008

Aerosol 1	H222-H229	Extremely flammable aerosol. Pressurised container: May burst if heated.
Eye Irrit. 2	H319	Causes serious eye irritation.
STOT SE 3	H336	May cause drowsiness or dizziness.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.
Aquatic Acute 1	H400	Very toxic to aquatic life.
Aquatic Chronic 1	H410	Very toxic to aquatic life with long lasting effects.

Response: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
IF exposed or concerned: Get medical advice/attention.

Storage: Store in a well-ventilated place. Keep cool.  
Store in a well-ventilated place. Keep container tightly closed.  
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

#### 2.2 Label elements

##### Labelling according to Regulation (EC) No 1272/2008

##### Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS02 GHS07 GHS09

##### Signal word

Danger

##### Hazard-determining components of labelling:

acetone  
reaction mass of ethylbenzole and xylene

(Contd. on page 2)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.02.2024

Version number 12 (replaces version 11)

Revision: 20.02.2024

**Trade name: Zinc Spray**

(Contd. of page 1)

· <u>Hazard statements</u>	Hydrocarbons, C9, aromatics propan-2-ol H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
	H319 Causes serious eye irritation.
	H336 May cause drowsiness or dizziness.
	H410 Very toxic to aquatic life with long lasting effects.
· <u>Precautionary statements</u>	P101 If medical advice is needed, have product container or label at hand.
	P102 Keep out of reach of children.
	P103 Read carefully and follow all instructions.
	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P211 Do not spray on an open flame or other ignition source.
	P251 Do not pierce or burn, even after use.
	P260 Do not breathe spray.
	P271 Use only outdoors or in a well-ventilated area.
	P273 Avoid release to the environment.
	P280 Wear protective gloves / eye protection.
	P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P403+P233 Store in a well-ventilated place. Keep container tightly closed.
	P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
	P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
· <u>Additional information:</u>	EUH066 Repeated exposure may cause skin dryness or cracking.
· <b>2.3 Other hazards</b>	
· <u>Results of PBT and vPvB assessment</u>	
· <u>PBT:</u>	Not applicable.
· <u>vPvB:</u>	Not applicable.
· <u>Determination of endocrine-disrupting properties</u>	For information on endocrine disrupting properties see section 11.

**SECTION 3: Composition/information on ingredients****3.2 Mixtures**· Description: Mixture of substances listed below with nonhazardous additions.· Dangerous components:

CAS: 7440-66-6 EINECS: 231-175-3 Index number: 030-001-01-9 Reg.nr.: 01-2119467174-37	zinc powder -zinc dust (stabilized) ----- Aquatic Acute 1, H400; Aquatic Chronic 1, H410	25-50%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49	acetone ----- Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	12.5-25%

(Contd. on page 3)

EU

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.02.2024

Version number 12 (replaces version 11)

Revision: 20.02.2024

**Trade name: Zinc Spray**

(Contd. of page 2)

CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	12.5-25%
EC number: 905-588-0 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32 01-2119486136-34	reaction mass of ethylbenzole and xylene Flam. Liq. 3, H226 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	1-5%
EC number: 918-668-5 Index number: 649-356-00-4 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H335-H336 EUH066	1-5%
CAS: 1314-13-2 EINECS: 215-222-5 Index number: 030-013-00-7 Reg.nr.: 01-2119463881-32	zinc oxide Aquatic Acute 1, H400; Aquatic Chronic 1, H410	1-5%
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25-xxxx	propan-2-ol Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	1-5%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane, pure Flam. Gas 1A, H220 Press. Gas (Comp.), H280	1-5%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures**· **4.1 Description of first aid measures**

- General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: Do not induce vomiting; call for medical help immediately.

· **4.2 Most important symptoms and effects, both acute and delayed**

Headache  
Dizziness  
Dizziness

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**SECTION 5: Firefighting measures**· **5.1 Extinguishing media**

- Suitable extinguishing agents: CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet

(Contd. on page 4)

EU

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 20.02.2024

Version number 12 (replaces version 11)

Revision: 20.02.2024

**Trade name:** Zinc Spray

(Contd. of page 3)

· **5.2 Special hazards arising from the substance or mixture**

In case of fire, the following can be released:  
Carbon monoxide (CO)  
Formation of toxic gases is possible during heating or in case of fire.

· **5.3 Advice for firefighters**

- Protective equipment:
- Additional information

Mount respiratory protective device.  
Cool endangered receptacles with water spray.  
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

### SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· **6.2 Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow product to reach sewage system or any water course.  
Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents  
Dispose contaminated material as waste according to section 13.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

Keep away from heat and direct sunlight.  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.

· Information about fire - and explosion protection:

Fumes can combine with air to form an explosive mixture.  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.  
Do not spray onto a naked flame or any incandescent material.

· **7.2 Conditions for safe storage, including any incompatibilities**

· Storage:

· Requirements to be met by storerooms and receptacles:

Store in a cool location.  
Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility:

Store away from foodstuffs.

· Further information about storage conditions:

Keep container tightly sealed.  
Do not seal receptacle gas tight.  
Store in cool, dry conditions in well sealed receptacles.  
Protect from heat and direct sunlight.

· Storage class:

2 B

(Contd. on page 5)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.02.2024

Version number 12 (replaces version 11)

Revision: 20.02.2024

**Trade name: Zinc Spray**

(Contd. of page 4)

· **7.3 Specific end use(s)** No further relevant information available.**SECTION 8: Exposure controls/personal protection**· **8.1 Control parameters**· Ingredients with limit values that require monitoring at the workplace:**67-64-1 acetone**IOELV Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm**reaction mass of ethylbenzole and xylene**AGW Short-term value: 442 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 221 mg/m<sup>3</sup>, 50 ppm  
H· DNELs**7440-66-6 zinc powder -zinc dust (stabilized)**

Oral	DNEL (Langzeit-wiederholt)	50 mg/kg bw/day (ARB)
Dermal	DNEL (Langzeit-wiederholt)	5,000 mg/kg bw/day (ARB)
		5,000 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	5 mg/m <sup>3</sup> Air (ARB)
		2.5 mg/m <sup>3</sup> Air (BEV)

**67-64-1 acetone**

Oral	DNEL (Langzeit-wiederholt)	62 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	186 mg/kg bw/day (ARB)
		62 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	2,420 mg/m <sup>3</sup> Air (ARB)
	DNEL (Langzeit-wiederholt)	1,210 mg/m <sup>3</sup> Air (ARB)
		200 mg/m <sup>3</sup> Air (BEV)

**reaction mass of ethylbenzole and xylene**

Oral	DNEL (Langzeit-wiederholt)	1.6 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	180-212 mg/kg bw/day (ARB)
		108 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	289-442 mg/m <sup>3</sup> Air (ARB)
		260 mg/m <sup>3</sup> Air (BEV)
		211-221 mg/m <sup>3</sup> Air (ARB)
	DNEL (Langzeit-wiederholt)	14.8-65.3 mg/m <sup>3</sup> Air (BEV)

**Hydrocarbons, C9, aromatics**

Oral	DNEL (Langzeit-wiederholt)	11 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	25 mg/kg bw/day (ARB)
		11 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	150 mg/m <sup>3</sup> Air (ARB)
		32 mg/m <sup>3</sup> Air (BEV)

**1314-13-2 zinc oxide**

Oral	DNEL (Langzeit-wiederholt)	0.83 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	83 mg/kg bw/day (ARB)
		83 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	5 mg/m <sup>3</sup> Air (ARB)
		2.5 mg/m <sup>3</sup> Air (BEV)

(Contd. on page 6)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.02.2024

Version number 12 (replaces version 11)

Revision: 20.02.2024

**Trade name: Zinc Spray**

(Contd. of page 5)

**67-63-0 propan-2-ol**

Oral	DNEL (Langzeit-wiederholt)	26 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	888 mg/kg bw/day (ARB)
		319 mg/kg bw/day (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	500 mg/m <sup>3</sup> Air (ARB)
		89 mg/m <sup>3</sup> Air (BEV)

## · PNECs

**7440-66-6 zinc powder -zinc dust (stabilized)**

PNEC (wässrig)	52 mg/l (KA)
	6.1 mg/l (MW)
	20.6 mg/l (SW)
PNEC (fest)	56.6 mg/kg Trockengew (BO)
	56.5 mg/kg Trockengew (MWS)
	118 mg/kg Trockengew (SWS)

**67-64-1 acetone**

PNEC (wässrig)	100 mg/l (KA)
	1.06 mg/l (MW)
	10.6 mg/l (SW)
	21 mg/l (WAS)
PNEC (fest)	29.5 mg/kg Trockengew (BO)
	3.04 mg/kg Trockengew (MWS)
	30.4 mg/kg Trockengew (SWS)

**reaction mass of ethylbenzole and xylene**

PNEC (wässrig)	6.58 mg/l (KA)
	0.327 mg/l (MW)
	0.327 mg/l (SW)
	0.327 mg/l (WAS)
PNEC (fest)	2.31 mg/kg Trockengew (BO)
	12.46 mg/kg Trockengew (MWS)
	12.46 mg/kg Trockengew (SWS)

**1314-13-2 zinc oxide**

PNEC (wässrig)	52 mg/l (KA)
	6.1 mg/l (MW)
	20.6 mg/l (SW)
PNEC (fest)	35.6 mg/kg Trockengew (BO)
	56.5 mg/kg Trockengew (MWS)
	117 mg/kg Trockengew (SWS)

**67-63-0 propan-2-ol**

PNEC (wässrig)	2,251 mg/l (KA)
	140.9 mg/l (MW)
	140.9 mg/l (SW)
	140.9 mg/l (WAS)
PNEC (fest)	28 mg/kg Trockengew (BO)
	552 mg/kg Trockengew (MWS)
	552 mg/kg Trockengew (SWS)

(Contd. on page 7)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.02.2024

Version number 12 (replaces version 11)

Revision: 20.02.2024


**Trade name: Zinc Spray**

(Contd. of page 6)

- Additional information: The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Do not inhale gases / fumes / aerosols.  
 Keep away from foodstuffs, beverages and feed.  
 Immediately remove all soiled and contaminated clothing  
 Wash hands before breaks and at the end of work.  
 Avoid contact with the eyes and skin.  
 Do not eat, drink, smoke or sniff while working.  
 Use skin protection cream for skin protection.  
 Clean skin thoroughly immediately after handling the product.
- Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Use suitable respiratory protective device in case of insufficient ventilation.  
Filter AX
- Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation  
 Preventive skin protection by use of skin-protecting agents is recommended.  
 After use of gloves apply skin-cleaning agents and skin cosmetics.  
 The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type.  
 The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.  
 This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).
- Material of gloves Butyl rubber, BR  
Nitrile rubber, NBR  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.
- Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.  
Value for the permeation: Level ≤ 6, 480 min
- As protection from splashes gloves made of the following materials are suitable: Butyl rubber, BR  
Butoject (KCL, Art\_No. 897, 898)  
Nitrile rubber, NBR

(Contd. on page 8)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.02.2024

Version number 12 (replaces version 11)

Revision: 20.02.2024

**Trade name: Zinc Spray**

(Contd. of page 7)

· Not suitable are gloves made of the following materials:

Leather gloves  
Strong material gloves

· Eye/face protection



Tightly sealed goggles

· Body protection:

Use protective suit.

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**General Information

· <u>Colour:</u>	Grey
· <u>Odour:</u>	Specific type
· <u>Melting point/freezing point:</u>	Undetermined.
· <u>Boiling point or initial boiling point and boiling range</u>	-44 °C
· <u>Lower and upper explosion limit</u>	
· <u>Lower:</u>	0.7 Vol %
· <u>Upper:</u>	13 Vol %
· <u>Flash point:</u>	-97 °C
· <u>Auto-ignition temperature:</u>	450 °C
· <u>pH</u>	Not determined. Not applicable
· <u>Viscosity:</u>	
· <u>Kinematic viscosity</u>	Not determined. Not applicable
· <u>Dynamic:</u>	Not determined. Not applicable
· <u>Solubility</u>	
· <u>water:</u>	Not miscible or difficult to mix.
· <u>Vapour pressure at 20 °C:</u>	5,100 hPa
· <u>Vapour pressure at 50 °C:</u>	>110 hPa
· <u>Density and/or relative density</u>	
· <u>Density at 20 °C:</u>	1.28 g/cm <sup>3</sup>

**9.2 Other information**

· <u>Appearance:</u>	
· <u>Form:</u>	Aerosol
· <u>Important information on protection of health and environment, and on safety.</u>	
· <u>Ignition temperature:</u>	Product is not selfigniting.
· <u>Explosive properties:</u>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <u>Solvent content:</u>	
· <u>Organic solvents:</u>	43.9 %
· <u>Solids content:</u>	8.4 %

Information with regard to physical hazard classes

· <u>Explosives</u>	Void
· <u>Flammable gases</u>	Void
· <u>Aerosols</u>	Extremely flammable aerosol. Pressurised container: May burst if heated.
· <u>Oxidising gases</u>	Void
· <u>Gases under pressure</u>	Void
· <u>Flammable liquids</u>	Void
· <u>Flammable solids</u>	Void

(Contd. on page 9)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.02.2024

Version number 12 (replaces version 11)

Revision: 20.02.2024

**Trade name: Zinc Spray**

(Contd. of page 8)

· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

**SECTION 10: Stability and reactivity**

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

**SECTION 11: Toxicological information**

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

**7440-66-6 zinc powder -zinc dust (stabilized)**

Oral	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4 h	>5.4 mg/l (rat)

**67-64-1 acetone**

Oral	LD50	5,800 mg/kg (rat) (OECD 401)
	NOEL	900 mg/kg (rat)
Dermal	LD50	15,688 mg/kg (rat)
		7,426-15,800 mg/kg (rabbit)
Inhalative	LC50/4 h	76 mg/l (rat)
	NOAEL	22,500 mg/m <sup>3</sup> (rat)
	LC50/48h	8,450 mg/l (crustaceans) 2,262 mg/l (daphnia magna)

**74-98-6 propane**

Inhalative	LC50/4 h	>20 mg/l (rat)
------------	----------	----------------

**reaction mass of ethylbenzole and xylene**

Oral	LD50	3,523 mg/kg (rat)
	NOAEL-Werte	250 mg/kg (rat)
Dermal	LD50	12,126 mg/kg (rabbit)
Inhalative	LC50/4h	29,000 mg/m <sup>3</sup> (rat)

(Contd. on page 10)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.02.2024

Version number 12 (replaces version 11)

Revision: 20.02.2024

**Trade name: Zinc Spray**

(Contd. of page 9)

	LC50/4 h	27.124 mg/l (rat)
<b>Hydrocarbons, C9, aromatics</b>		
Oral	LD50	3,595 mg/kg (rat) (OECD 401)
Dermal	LD50	>3,160 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/4 h	>6,193 mg/l (rat)
<b>1314-13-2 zinc oxide</b>		
Oral	LD50	7,950 mg/kg (mouse) >5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4 h	>5,700 mg/l (rat)
<b>67-63-0 propan-2-ol</b>		
Oral	LD50	>2,000 mg/kg (rabbit) 5,840 mg/kg (rat) (OECD 401)
	NOAEL-Werte	400 mg/kg (rat)
Dermal	LD50	13,900 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/8h	47.5 ppm (rat)
	LC50/4 h	>25 mg/l (rat)
	LC50	25,000 mg/m <sup>3</sup> (rat)
	LC50/48h	>100 mg/l (Leuciscus idus)
<b>106-97-8 butane, pure</b>		
Inhalative	LC50/4 h	658 mg/l (rat)

- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard May be fatal if swallowed and enters airways.

**11.2 Information on other hazards**

- Endocrine disrupting properties

None of the ingredients is listed.

**SECTION 12: Ecological information****12.1 Toxicity**

- Aquatic toxicity:

**7440-66-6 zinc powder -zinc dust (stabilized)**

EC50/96h	0.527 mg/l (algae)
EC50/48h	0.353 mg/l (daphnia magna)
NOEC	0.017 mg/kg (Pseudokirchneriella subcapitata)
NOELR/72h	0.0729 mg/l (Pseudokirchneriella subcapitata)
NOEC/21d	178 mg/l (KA)
NOELR/28d	0.0083 mg/l (Cyprinus carpio)
EC10	0.0273 mg/l (algae)
	0.0592 mg/l (daphnia magna)

(Contd. on page 11)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.02.2024

Version number 12 (replaces version 11)

Revision: 20.02.2024

**Trade name: Zinc Spray**

(Contd. of page 10)

EC50/48h	1 mg/l (daphnia magna)
EC50/72h	0.17 mg/l (Selenastrum capricornutum)
LC50/96h	0.41 mg/l (Oncorhynchus mykiss)
	0.238-0.269 mg/l (Pimephales promelas)

**67-64-1 acetone**

EC50/96h	7,200 mg/l (algae)
	8,300 mg/l (piscis)
	8,300 mg/l (Iepomis macrochirus)
	7,500 mg/l (selenastrum capricornutum)
EC50	1,700 mg/l (bacteria)
LC50	6,368 mg/l (piscis)
LC50/24h	8,800 mg/l (daphnia)
EC5/16h	1,700 mg/l (pseudomonas putida)
EC5/72h	28 mg/l (Entosiphon sulcatum)
EC5/8d	530 mg/l (microorganisms)
IC5/8d	7,500 mg/l (Scenedesmus quadricauda)
EC50/48h	3,400 mg/l (algae)
	8,800 mg/l (daphnia magna)
NOEC	1,700 mg/kg (pseudomonas putida)
	4,740 mg/kg (selenastrum capricornutum)
NOELR/28d	2,212 mg/l (daphnia magna)
EC50/48h	12,600 mg/l (Danio rerio.)
	8,800 mg/l (daphnia magna)
LC50/96h	8,300 mg/l (Iem)
	8,300 mg/l (Iepomis macrochirus)
	7,500 mg/l (Leuciscus idus)
	5,540 mg/l (Oncorhynchus mykiss)
	8,120 mg/l (Pimephales promelas)

**reaction mass of ethylbenzole and xylene**

LC50/24h	1 mg/l (daphnia magna) (OECD 202)
EC50/48h	3.2-9.5 mg/l (daphnia magna) (US EPA)
ErC50/72h	4.9 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
NOEC	16 mg/l (BES)
	1.3 mg/l (Oncorhynchus mykiss)
NOELR/72h	0.44 mg/l (algae)
NOEC/21d	1.57 mg/l (daphnia magna) (OECD 211)
NOELR/28d	16 mg/l (bacteria)
EC50/72h	1-10 mg/l (algae)
	2.2 mg/l (selenastrum capricornutum) (OECD 201)
LC50/96h	1-10 mg/l (fish)
	86 mg/l (Leuciscus idus)
	2.6 mg/l (Oncorhynchus mykiss) (OECD 203)
	8.9-16.4 mg/l (pimephales promelas)

**Hydrocarbons, C9, aromatics**

EC50/96h	9.2 mg/l (Oncorhynchus mykiss)
----------	--------------------------------

(Contd. on page 12)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.02.2024

Version number 12 (replaces version 11)

Revision: 20.02.2024

**Trade name: Zinc Spray**

(Contd. of page 11)

LC50	1-10 mg/l (daphnia magna)
ErC50/72h	0.42 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
EL50/48h	3.2 mg/l (daphnia magna) (OECD 202)
EL50/72h	2.6-2.9 mg/l (Pseudokirchneriella subcapitata) 2.9 mg/l (selenastrum capricornutum)
LL50/96h	9.2 mg/l (Oncorhynchus mykiss) (OECD 203)
NOELR/72h	1 mg/l (Pseudokirchneriella subcapitata)
EC50/48h	7.4 mg/l (daphnia magna)
EC50/72h	0.29 mg/l (Pseudokirchneriella subcapitata) (OECD 201)

**1314-13-2 zinc oxide**

EC50/48h	>1,000 mg/l (daphnia magna)
NOELR/72h	0.017 mg/l (Pseudokirchneriella subcapitata)
EC50/48h	1 mg/l (daphnia magna)
EC50/72h	0.17 mg/l (selenastrum capricornutum)
LC50/96h	>320 mg/l (lem) 1.1 mg/l (Oncorhynchus mykiss) 2,246 mg/l (pimephales promelas)
LC50/72h	0.17 mg/l (Selenastrum capricornutum)

**67-63-0 propan-2-ol**

EC50/24h	9,714 mg/l (daphnia magna)
EC50	>1,000 mg/l (BES)
LC50/24h	9,714 mg/l (daphnia magna)
EC50/15min	22,000 mg/l (Photobac. phosphoreum)
IC50/72h	>1,000 mg/l (Desmodemus subspicatus)
EC10/18h	5,175 mg/l (pseudomonas putida) (DIN 38412)
EC50/48h	9,714 mg/l (daphnia magna) (OECD 202)
EC50/72h	>1,000 mg/l (algae) >100 mg/l (Scenedesmus subspicatus)
LC50/96h	6,550 mg/l (piscis) 9,640 mg/l (Pimephales promelas)

**12.2 Persistence and degradability**

Easily biodegradable

**12.3 Bioaccumulative potential**

No further relevant information available.

**12.4 Mobility in soil**

No further relevant information available.

**12.5 Results of PBT and vPvB assessment**

· PBT: Not applicable.

· vPvB: Not applicable.

**12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

**12.7 Other adverse effects**

· Remark: Very toxic for fish

· Additional ecological information:

· General notes:

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

Do not allow product to reach ground water, water course or sewage system.

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

(Contd. on page 13)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.02.2024

Version number 12 (replaces version 11)

Revision: 20.02.2024

**Trade name: Zinc Spray**

(Contd. of page 12)

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

- Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

· Uncleaned packaging:

- Recommendation: Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

**SECTION 14: Transport information****14.1 UN number or ID number**

- ADR, IMDG, IATA UN1950

**14.2 UN proper shipping name**

- ADR 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS
- IMDG AEROSOLS, MARINE POLLUTANT
- IATA AEROSOLS, flammable

**14.3 Transport hazard class(es)**· ADR

- Class 2 5F Gases.
- Label 2.1

· IMDG

- Class 2.1 Gases.
- Label 2.1

· IATA

- Class 2.1 Gases.
- Label 2.1

**14.4 Packing group**

- ADR, IMDG, IATA Void

**14.5 Environmental hazards:**

- Marine pollutant: Product contains environmentally hazardous substances:

Symbol (fish and tree)

(Contd. on page 14)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.02.2024

Version number 12 (replaces version 11)

Revision: 20.02.2024

**Trade name: Zinc Spray**

(Contd. of page 13)

· <u>Special marking (ADR):</u>	Symbol (fish and tree)
· <b>14.6 Special precautions for user</b>	Warning: Gases.
· <u>Hazard identification number (Kemler code):</u>	-
· <u>EMS Number:</u>	F-D,S-U
· <u>Stowage Code</u>	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· <u>Segregation Code</u>	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· <b>14.7 Maritime transport in bulk according to IMO instruments</b>	Not applicable.
· <u>Transport/Additional information:</u>	
· <u>ADR</u>	1L
· <u>Limited quantities (LQ)</u>	Code: E0
· <u>Excepted quantities (EQ)</u>	Not permitted as Excepted Quantity
· <u>Transport category</u>	2
· <u>Tunnel restriction code</u>	D
· <u>IMDG</u>	1L
· <u>Limited quantities (LQ)</u>	Code: E0
· <u>Excepted quantities (EQ)</u>	Not permitted as Excepted Quantity
· <u>UN "Model Regulation":</u>	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I
- Seveso category
  - None of the ingredients is listed.
  - E1 Hazardous to the Aquatic Environment
  - P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

(Contd. on page 15)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.02.2024

Version number 12 (replaces version 11)

Revision: 20.02.2024

**Trade name: Zinc Spray**

(Contd. of page 14)

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

67-64-1 acetone

· Regulation (EC) No 273/2004 on drug precursors

67-64-1 acetone

3

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

67-64-1 acetone

3

· National regulations:

· Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· VOC EU 568.1 g/l

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

· Department issuing SDS: Laboratory

· Date of previous version: 03.08.2022

· Version number of previous version: 11

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
 ICAO: International Civil Aviation Organisation  
 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 DNEL: Derived No-Effect Level (REACH)  
 PNEC: Predicted No-Effect Concentration (REACH)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 SVHC: Substances of Very High Concern  
 vPvB: very Persistent and very Bioaccumulative  
 ATE: Acute toxicity estimate values  
 Flam. Gas 1A: Flammable gases – Category 1A  
 Aerosol 1: Aerosols – Category 1  
 Press. Gas (Comp.): Gases under pressure – Compressed gas  
 Flam. Liq. 2: Flammable liquids – Category 2  
 Flam. Liq. 3: Flammable liquids – Category 3  
 Acute Tox. 4: Acute toxicity – Category 4  
 Skin Irrit. 2: Skin corrosion/irritation – Category 2  
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

(Contd. on page 16)

EU

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.02.2024

Version number 12 (replaces version 11)

Revision: 20.02.2024

**Trade name: Zinc Spray**

(Contd. of page 15)

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

EU