

# Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.11.2025

Version number 33 (replaces version 32)

Revision: 17.11.2025

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name: **Multi Talent 2K-UHS Filler 4:1**

Article number: 70502, 70504, 70448

UFI: EX21-30DV-900T-4GNM

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Coating

### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH  
Lechstrasse 28  
D 90451 Nürnberg

Tel. +49(0)911-642960  
Fax. +49(0)911-644456  
e-mail info@akemi.de

Further information obtainable from:

Laboratory

### 1.4 Emergency telephone number:

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH  
Tel. +49(0)911-64296-59  
Reachable during the following office hours:  
Monday – Thursday from 07:30 a.m. to 16:30 p.m.  
Friday from 07:30 a.m. to 13:30 p.m.

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

Response: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

Storage: Store in a well-ventilated place. Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Store locked up.

### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictograms

The product is classified and labelled according to the CLP regulation.



GHS02

Signal word

Warning

Hazard-determining components of labelling:

Not applicable.

Hazard statements

H226 Flammable liquid and vapour.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101

If medical advice is needed, have product container or label at hand.

P102

Keep out of reach of children.

P103

Read carefully and follow all instructions.

(Contd. on page 2)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.11.2025

Version number 33 (replaces version 32)

Revision: 17.11.2025

**Trade name: Multi Talent 2K-UHS Filler 4:1**

(Contd. of page 1)

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**2.3 Other hazards****Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

**Determination of endocrine-disrupting properties**

For information on endocrine disrupting properties see section 11.

**SECTION 3: Composition/information on ingredients****3.2 Mixtures**

· **Description:** Mixture: consisting of the following components.

**Dangerous components:**

CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29	n-butyl acetate Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	12.5-25%
EC number: 905-588-0 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32 01-2119486136-34	reaction mass of ethylbenzole and xylene Flam. Liq. 3, H226 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 Aquatic Chronic 3, H412	<10%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226 STOT SE 3, H336	1-5%
CAS: 64742-95-6 EC number: 918-668-5 Index number: 649-356-00-4 Reg.nr.: 01-2119455851-35	Solvent naphtha (petroleum), light arom. Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H335-H336 EUH066	1-5%
CAS: 122-51-0 EINECS: 204-550-4 Reg.nr.: 01-2119438191-46	triethoxymethane Flam. Liq. 3, H226	1-5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures****4.1 Description of first aid measures**

· **General information:** Take affected persons out into the fresh air.

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** If skin irritation continues, consult a doctor.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

(Contd. on page 3)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.11.2025

Version number 33 (replaces version 32)

Revision: 17.11.2025

**Trade name:** Multi Talent 2K-UHS Filler 4:1

(Contd. of page 2)

- After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**
  - Breathing difficulty
  - Dizziness
  - Headache
  - Dizziness
  - Nausea
- Hazards
  - Danger of impaired breathing.
- **4.3 Indication of any immediate medical attention and special treatment needed**
  - If swallowed, gastric irrigation with added, activated carbon.
  - If swallowed or in case of vomiting, danger of entering the lungs.

**SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
- Suitable extinguishing agents: CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
  - Formation of toxic gases is possible during heating or in case of fire.
  - In case of fire, the following can be released:
  - Carbon monoxide (CO)
  - Under certain fire conditions, traces of other toxic gases cannot be excluded.
- **5.3 Advice for firefighters**
- Protective equipment:
  - Wear self-contained respiratory protective device.
  - Do not inhale explosion gases or combustion gases.
  - Wear fully protective suit.
- Additional information
  - Cool endangered receptacles with water spray.
  - Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

**SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**
  - Ensure adequate ventilation
  - Keep away from ignition sources.
  - Use respiratory protective device against the effects of fumes/dust/aerosol.
  - Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
  - Do not allow product to reach sewage system or any water course.
  - Inform respective authorities in case of seepage into water course or sewage system.
  - Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
  - Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
  - Ensure adequate ventilation.
- **6.4 Reference to other sections**
  - See Section 7 for information on safe handling.
  - See Section 8 for information on personal protection equipment.
  - See Section 13 for disposal information.

(Contd. on page 4)

EU

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.11.2025

Version number 33 (replaces version 32)

Revision: 17.11.2025

**Trade name:** Multi Talent 2K-UHS Filler 4:1

(Contd. of page 3)

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

Keep receptacles tightly sealed.  
 Store in cool, dry place in tightly closed receptacles.  
 Keep away from heat and direct sunlight.  
 Use only in well ventilated areas.  
 Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).  
 Ensure good ventilation/exhaustion at the workplace.

**Information about fire - and explosion protection:**

Fumes can combine with air to form an explosive mixture.  
 Keep ignition sources away - Do not smoke.  
 Protect against electrostatic charges.

**7.2 Conditions for safe storage, including any incompatibilities****Storage:****Requirements to be met by storerooms and receptacles:**

Store only in the original receptacle.  
 Prevent any seepage into the ground.

**Information about storage in one common storage facility:**

Store away from foodstuffs.

**Further information about storage conditions:**

Store receptacle in a well ventilated area.  
 Protect from frost.  
 Keep container tightly sealed.

**Storage class:**

3

**7.3 Specific end use(s)**

No further relevant information available.

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Ingredients with limit values that require monitoring at the workplace:****123-86-4 n-butyl acetate**

IOELV	Short-term value: 723 mg/m <sup>3</sup> , 150 ppm Long-term value: 241 mg/m <sup>3</sup> , 50 ppm
-------	--

**reaction mass of ethylbenzole and xylene**

AGW	Short-term value: 442 mg/m <sup>3</sup> , 100 ppm Long-term value: 221 mg/m <sup>3</sup> , 50 ppm H
-----	---

**108-65-6 2-methoxy-1-methylethyl acetate**

IOELV	Short-term value: 550 mg/m <sup>3</sup> , 100 ppm Long-term value: 275 mg/m <sup>3</sup> , 50 ppm Skin
-------	--

**64742-95-6 Solvent naphtha (petroleum), light arom.**

OEL	Long-term value: 100 mg/m <sup>3</sup> , 20 ppm
-----	---

**DNELs****123-86-4 n-butyl acetate**

Oral	DNEL (Kurzzeit-akut)	2 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	2 mg/kg bw/day (BEV)
Dermal	DNEL (Kurzzeit-akut)	11 mg/kg bw/day (ARB)
		6 mg/kg bw/day (BEV)

(Contd. on page 5)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.11.2025

Version number 33 (replaces version 32)

Revision: 17.11.2025

**Trade name: Multi Talent 2K-UHS Filler 4:1**

(Contd. of page 4)

Inhalative	DNEL ( Langzeit-wiederholt)	11 mg/kg bw/day (ARB) 6 mg/kg bw/day (BEV)
	DNEL (Kurzzeit-akut)	600 mg/m <sup>3</sup> Air (ARB) 300 mg/m <sup>3</sup> Air (BEV)
	DNEL (Langzeit-wiederholt)	300 mg/m <sup>3</sup> Air (ARB) 35.7 mg/m <sup>3</sup> Air (BEV)

**reaction mass of ethylbenzole and xylole**

Oral	DNEL (Langzeit-wiederholt)	1.6 mg/kg bw/day (BEV)
Dermal	DNEL ( Langzeit-wiederholt)	180 mg/kg bw/day (ARB) 108 mg/kg bw/day (BEV)
	DNEL (Kurzzeit-akut)	289 mg/m <sup>3</sup> Air (ARB) 174 mg/m <sup>3</sup> Air (BEV)
Inhalative	DNEL (Langzeit-wiederholt)	77-221 mg/m <sup>3</sup> Air (ARB) 14.8-174 mg/m <sup>3</sup> Air (BEV)

**108-65-6 2-methoxy-1-methylethyl acetate**

Oral	DNEL (Kurzzeit-akut)	500 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	1.67 mg/kg bw/day (BEV)
	DNEL ( Langzeit-wiederholt)	796 mg/kg bw/day (ARB) 54.8 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	550 mg/m <sup>3</sup> Air (ARB) 33 mg/m <sup>3</sup> Air (BEV)
	DNEL (Langzeit-wiederholt)	275 mg/m <sup>3</sup> Air (ARB) 33 mg/m <sup>3</sup> Air (BEV)

**64742-95-6 Solvent naphtha (petroleum), light arom.**

Oral	DNEL (Langzeit-wiederholt)	11 mg/kg bw/day (BEV)
Dermal	DNEL ( Langzeit-wiederholt)	25 mg/kg bw/day (ARB) 11 mg/kg bw/day (BEV)
	DNEL (Langzeit-wiederholt)	150 mg/m <sup>3</sup> Air (ARB) 32 mg/m <sup>3</sup> Air (BEV)

## · PNECs

**123-86-4 n-butyl acetate**

PNEC (wässrig)	35.6 mg/l (KA)
	0.018 mg/l (MW)
	0.18 mg/l (SW)
	0.36 mg/l (WAS)
PNEC (fest)	0.0903 mg/kg Trockengew (BO)
	0.0981 mg/kg Trockengew (MWS)
	0.981 mg/kg Trockengew (SWS)

**reaction mass of ethylbenzole and xylole**

PNEC (wässrig)	1.6 mg/l (KA)
	0.004 mg/l (MW)
	0.044 mg/l (SW)
	0.01 mg/l (WAS)
PNEC (fest)	0.852 mg/kg Trockengew (BO)
	0.252 mg/kg Trockengew (MWS)

(Contd. on page 6)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.11.2025

Version number 33 (replaces version 32)

Revision: 17.11.2025

**Trade name: Multi Talent 2K-UHS Filler 4:1**

(Contd. of page 5)

	2.52 mg/kg Trockengew (SWS)
<b>108-65-6 2-methoxy-1-methylethyl acetate</b>	
PNEC (wässrig)	100 mg/l (KA) 0.0635 mg/l (MW) 0.635 mg/l (SW) 6.35 mg/l (WAS)
PNEC (fest)	0.29 mg/kg Trockengew (BO) 0.329 mg/kg Trockengew (MWS) 3.29 mg/kg Trockengew (SWS)

· Additional information: The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· Appropriate engineering controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and hygienic measures:

Do not eat, drink, smoke or sniff while working.  
Apply solvent resistant skin cream before starting work.  
Use skin protection cream for skin protection.  
Clean skin thoroughly immediately after handling the product.  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.

· Respiratory protection:

Filter A/P2  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection

Preventive skin protection by use of skin-protecting agents is recommended.  
After use of gloves apply skin-cleaning agents and skin cosmetics.



Protective gloves

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times' data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory analyses of the company KCL GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: <http://www.kcl.de>).

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 7)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31


Printing date 17.11.2025

Version number 33 (replaces version 32)

Revision: 17.11.2025

**Trade name: Multi Talent 2K-UHS Filler 4:1**

(Contd. of page 6)

- Penetration time of glove material Value for the permeation: Level  $\leq$  6, 480 min  
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- For the permanent contact gloves made of the following materials are suitable: Butyl rubber, BR  
Butoject (KCL, Art\_No. 897, 898)
- As protection from splashes gloves made of the following materials are suitable: Butyl rubber, BR  
Butoject (KCL, Art\_No. 897, 898)  
Nitrile rubber, NBR  
Camatril (KCL, 730, 731, 732, 733)
- Not suitable are gloves made of the following materials: Strong material gloves  
Leather gloves
- Eye/face protection  Tightly sealed goggles
- Body protection: Solvent resistant protective clothing

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**

- General Information
- Colour: According to product specification
- Odour: Characteristic
- Odour threshold: Not determined.
- Melting point/freezing point: Undetermined.
- Boiling point or initial boiling point and boiling range 36 °C
- Flammability Not applicable.
- Lower and upper explosion limit
- Lower: 3 Vol %
- Upper: 10.4 Vol %
- Flash point: 27 °C
- Auto-ignition temperature: 370 °C
- Decomposition temperature: Not determined.
- pH Not determined.
- Viscosity:
- Kinematic viscosity Not determined.
- Dynamic at 20 °C: 3,800 mPas
- Solubility
- water: Not miscible or difficult to mix.
- Partition coefficient n-octanol/water (log value) Not determined.
- Vapour pressure at 20 °C: 10.7 hPa
- Vapour pressure at 50 °C: 55 hPa
- Density and/or relative density
- Density at 20 °C: 1.54 g/cm<sup>3</sup>
- Relative density Not determined.
- Vapour density Not determined.

**9.2 Other information**

- Appearance:
- Form: Fluid

(Contd. on page 8)

EU

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.11.2025

Version number 33 (replaces version 32)

Revision: 17.11.2025

**Trade name: Multi Talent 2K-UHS Filler 4:1**

(Contd. of page 7)

- Important information on protection of health and environment, and on safety.
- Ignition temperature: Product is not selfigniting.
- Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- Solvent content:
- Organic solvents: 30.2 %
- Solids content: 53.5 %
- Change in condition
- Evaporation rate Not determined.

- Information with regard to physical hazard classes
- Explosives Void
- Flammable gases Void
- Aerosols Void
- Oxidising gases Void
- Gases under pressure Void
- Flammable liquids Flammable liquid and vapour.
- Flammable solids Void
- Self-reactive substances and mixtures Void
- Pyrophoric liquids Void
- Pyrophoric solids Void
- Self-heating substances and mixtures Void
- Substances and mixtures, which emit flammable gases in contact with water Void
- Oxidising liquids Void
- Oxidising solids Void
- Organic peroxides Void
- Corrosive to metals Void
- Desensitised explosives Void

**SECTION 10: Stability and reactivity**

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- Thermal decomposition / conditions to be avoided: No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions** Reacts with acids, alkalis and oxidising agents.  
Reacts with strong oxidising agents.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide and carbon dioxide  
Nitrogen oxides (NO<sub>x</sub>)

**SECTION 11: Toxicological information**

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:**ATE (Acute Toxicity Estimates)**

Dermal	ATE mix	12,261 mg/kg
Inhalative	LC50/4 h	123 mg/l (rat)

(Contd. on page 9)

EU

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.11.2025

Version number 33 (replaces version 32)

Revision: 17.11.2025

**Trade name:** Multi Talent 2K-UHS Filler 4:1

(Contd. of page 8)

**123-86-4 n-butyl acetate**

Oral	LD50	10,760 mg/kg (rat) (OECD 423)
Dermal	LD50	14,112 mg/kg (rat) (OECD 402)
Inhalative	LC50/4 h	>21 mg/l (rat) (OECD 403)
	LC50	390 mg/m <sup>3</sup> (rat)
	LC50/48h	64 mg/l (Brachydanio rerio)

**reaction mass of ethylbenzole and xylene**

Oral	LD50	3,523 mg/kg (rat)
	NOAEL-Werte	250 mg/kg (rat)
Dermal	LD50	12,126 mg/kg (rabbit)
	ATE mix	1,100 mg/kg (rabbit)
Inhalative	LC50/4h	29,000 mg/m <sup>3</sup> (rat)
	LC50/4 h	11 mg/l (rat)

**108-65-6 2-methoxy-1-methylethyl acetate**

Oral	LD50	8,500 mg/kg (rat) (OECD 401)
	NOAEL-Werte	1,500 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit) (OECD 402)
		>2,000 mg/kg (rat)
Inhalative	LC50/4h	>10,000 mg/m <sup>3</sup> (rat)
	LC50	>23.8 mg/l (rat)
	LC50/4 h	35.7 mg/l (rat)
	LC50/48h	100 mg/l (Desmodesmus subspicatus)

**64742-95-6 Solvent naphtha (petroleum), light arom.**

Oral	LD50	3,592 mg/kg (rat)
Dermal	LD50	>3,160 mg/kg (rabbit)
		>2,000 mg/kg (rat)

**122-51-0 triethoxymethane**

Oral	LD50	7,060 mg/kg (rat)
Dermal	LD50	18,000 mg/kg (rabbit)
	LC50/48h	592 mg/l (Leuciscus idus) (DIN 38412-15)

· Primary irritant effect:· Skin corrosion/irritation

Based on available data, the classification criteria are not met.

· Serious eye damage/irritation

Based on available data, the classification criteria are not met.

· Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

· Germ cell mutagenicity

Based on available data, the classification criteria are not met.

· Carcinogenicity

Based on available data, the classification criteria are not met.

· Reproductive toxicity

Based on available data, the classification criteria are not met.

· STOT-single exposure

Based on available data, the classification criteria are not met.

· STOT-repeated exposure

Based on available data, the classification criteria are not met.

· Aspiration hazard

Based on available data, the classification criteria are not met.

· **11.2 Information on other hazards**· Endocrine disrupting properties

None of the ingredients is listed.

(Contd. on page 10)

EU

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.11.2025

Version number 33 (replaces version 32)

Revision: 17.11.2025

**Trade name: Multi Talent 2K-UHS Filler 4:1**

(Contd. of page 9)

**SECTION 12: Ecological information****· 12.1 Toxicity****· Aquatic toxicity:****123-86-4 n-butyl acetate**

EC50/24h	72.8 mg/l (daphnia magna) (DIN 38412)
EC50/96h	320 mg/l (algae)
LC50/24h	205 mg/l (daphnia magna)
IC50/72h	648 mg/l (Desmodesmus subspicatus)
EC10/18h	959 mg/l (pseudomonas putida)
EC50/48h	44 mg/l (daphnia magna) (OECD 202)
ErC50/72h	675 mg/l (Scenedesmus subspicatus)
EC50/16h	959 mg/l (pseudomonas putida)
NOEC	200 mg/kg (Desmodesmus subspicatus)
NOEC/21d	23 mg/l (daphnia magna) (OECD 211)
EC50/72h	647.7 mg/l (Desmodesmus subspicatus) (Zellvermehrungshemmtest)
	397 mg/l (Scenedesmus subspicatus)
LC50/96h	62 mg/l (Danio rerio.)
	81 mg/l (piscis)
	100 mg/l (Iepomis macrochirus)
	62 mg/l (Leuciscus idus) (DIN 38412)
	mg/l (Oncorhynchus mykiss)
	18 mg/l (pimephales promelas) (OECD 203)

**reaction mass of ethylbenzole and xylole**

LC50/24h	1 mg/l (daphnia magna) (OECD 202)
EC50/48h	3.2-9.5 mg/l (daphnia magna) (US EPA)
ErC50/72h	4.9 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
NOEC	16 mg/l (BES)
	1.3 mg/l (Oncorhynchus mykiss)
NOELR/72h	0.44 mg/l (Pseudokirchneriella subcapitata)
NOEC/21d	1.57 mg/l (daphnia magna) (OECD 211)
NOELR/28d	16 mg/l (bacteria)
EC50/72h	1-10 mg/l (algae)
	4.7 mg/l (selenastrum capricornutum) (OECD 201)
LC50/96h	1-10 mg/l (fish)
	86 mg/l (Leuciscus idus)
	2.6 mg/l (Oncorhynchus mykiss) (OECD 203)
	8.9-16.4 mg/l (pimephales promelas)

**108-65-6 2-methoxy-1-methylethyl acetate**

EC50	>500 mg/l (daphnia magna)
LC50	>100 mg/l (Oryzias latipes)
EC50/48h	>500 mg/l (daphnia magna) (RL 67/548/EWG. Anhang V, C.2.)
ErC50/72h	>1,000 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
EC20/0.5h	>1,000 mg/l (BES) (OECD 209)
NOEC	47.5 mg/l (Oryzias latipes)

(Contd. on page 11)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.11.2025

Version number 33 (replaces version 32)

Revision: 17.11.2025

**Trade name: Multi Talent 2K-UHS Filler 4:1**

(Contd. of page 10)

NOEC/21d	≥100 mg/l (daphnia magna)
EC10	>1,000 mg/l (BES)
EC50/72h	>1,000 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	100-180 mg/l (Oncorhynchus mykiss)
	>100 mg/l (Oryzias latipes)
	161 mg/l (Pimephales promelas)

**64742-95-6 Solvent naphtha (petroleum), light arom.**

EC50	<10 mg/l (daphnia magna)
IC50	<10 mg/l (daphnia magna)
LC50	<10 mg/l (algae)
	>1-<10 mg/l (piscis)
EL50/48h	3.2 mg/l (ceriodaphnia Dubai)
	3.2 mg/l (daphnia magna)
EL50/72h	2.6-2.9 mg/l (Pseudokirchneriella subcapitata)
	2.9 mg/l (selenastrum capricornutum)
LL50/96h	9.2 mg/l (Oncorhynchus mykiss)
NOELR/72h	1 mg/l (Pseudokirchneriella subcapitata)
EC50/48h	3.2 mg/l (daphnia magna)
EC50/72h	2.9 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	9.2 mg/l (Oncorhynchus mykiss)

**122-51-0 triethoxymethane**

LC 0/48h	400 mg/l (Leuciscus idus) (DIN 38412-15)
EC50/48h	617 mg/l (daphnia magna) (92/69/EWG)
EC10/5h	1,400 mg/l (bacteria)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- PBT: Not applicable.
- vPvB: Not applicable.
- **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- Remark: Toxic for fish
- Additional ecological information:
- General notes: Toxic for aquatic organisms  
Do not allow product to reach ground water, water course or sewage system.  
Also poisonous for fish and plankton in water bodies.  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

**SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods**
- Recommendation: Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packaging:
- Recommendation: Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

(Contd. on page 12)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.11.2025

Version number 33 (replaces version 32)

Revision: 17.11.2025

**Trade name:** Multi Talent 2K-UHS Filler 4:1

(Contd. of page 11)

· Recommended cleansing agents: Alcohol

**SECTION 14: Transport information****· 14.1 UN number or ID number**

· ADR, IMDG, IATA UN1263

**· 14.2 UN proper shipping name**· ADR 1263 PAINT RELATED MATERIAL  
· IMDG, IATA PAINT RELATED MATERIAL**· 14.3 Transport hazard class(es)**

· ADR

· Class 3 (F1) Flammable liquids.  
· Label 3

· IMDG, IATA

· Class 3 Flammable liquids.  
· Label 3**· 14.4 Packing group**

· ADR, IMDG, IATA III

**· 14.5 Environmental hazards:**

· Marine pollutant: No

**· 14.6 Special precautions for user**Warning: Flammable liquids.  
· Hazard identification number (Kemler code): 30  
· EMS Number: F-E, S-E  
· Stowage Category A**· 14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 5L  
· Excepted quantities (EQ) Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml

· Transport category 3

· Tunnel restriction code D/E

· IMDG

· Limited quantities (LQ) 5L  
· Excepted quantities (EQ) Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 13)

## Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.11.2025

Version number 33 (replaces version 32)

Revision: 17.11.2025

**Trade name:** Multi Talent 2K-UHS Filler 4:1

(Contd. of page 12)

<u>UN "Model Regulation":</u>	UN 1263 PAINT RELATED MATERIAL, 3, III
-------------------------------	--

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I                      None of the ingredients is listed.
- Seveso category    P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements                      5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements                      50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII                      Conditions of restriction: 3

<u>DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II</u>	None of the ingredients is listed.
---	------------------------------------

<u>REGULATION (EU) 2019/1148</u>	None of the ingredients is listed.
----------------------------------	------------------------------------

<u>Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))</u>	None of the ingredients is listed.
---	------------------------------------

<u>Annex II - REPORTABLE EXPLOSIVES PRECURSORS</u>	None of the ingredients is listed.
--	------------------------------------

<u>Regulation (EC) No 273/2004 on drug precursors</u>	None of the ingredients is listed.
---	------------------------------------

<u>Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors</u>	None of the ingredients is listed.
---	------------------------------------

<u>Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors</u>	None of the ingredients is listed.
---	------------------------------------

<u>National regulations:</u>	
------------------------------	--

<u>Information about limitation of use:</u>	Employment restrictions concerning pregnant and lactating women must be observed. Employment restrictions concerning juveniles must be observed.
---	---

<u>Waterhazard class:</u>	Water hazard class 1 (Self-assessment): slightly hazardous for water.
---------------------------	---

<u>Substances of very high concern (SVHC) according to REACH, Article 57</u>	None of the ingredients is listed.
--	------------------------------------

<u>VOC EU</u>	467.1 g/l
---------------	-----------

<u>15.2 Chemical safety assessment:</u>	A Chemical Safety Assessment has not been carried out.
---	--

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

<u>Department issuing SDS:</u>	Laboratory
--------------------------------	------------

(Contd. on page 14)

## Safety data sheet

### according to Regulation (EC) No 1907/2006, Article 31

Printing date 17.11.2025

Version number 33 (replaces version 32)

Revision: 17.11.2025

**Trade name: Multi Talent 2K-UHS Filler 4:1**

(Contd. of page 13)

<ul style="list-style-type: none"> <li>· <u>Date of previous version:</u></li> <li>· <u>Version number of previous version:</u></li> <li>· <u>Abbreviations and acronyms:</u></li> </ul>	<p>23.02.2024</p> <p>32</p> <p>RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)</p> <p>ICAO: International Civil Aviation Organisation</p> <p>ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)</p> <p>IMDG: International Maritime Code for Dangerous Goods</p> <p>IATA: International Air Transport Association</p> <p>GHS: Globally Harmonised System of Classification and Labelling of Chemicals</p> <p>EINECS: European Inventory of Existing Commercial Chemical Substances</p> <p>ELINCS: European List of Notified Chemical Substances</p> <p>CAS: Chemical Abstracts Service (division of the American Chemical Society)</p> <p>DNEL: Derived No-Effect Level (REACH)</p> <p>PNEC: Predicted No-Effect Concentration (REACH)</p> <p>LC50: Lethal concentration, 50 percent</p> <p>LD50: Lethal dose, 50 percent</p> <p>PBT: Persistent, Bioaccumulative and Toxic</p> <p>SVHC: Substances of Very High Concern</p> <p>vPvB: very Persistent and very Bioaccumulative</p> <p>ATE: Acute toxicity estimate values</p> <p>Flam. Liq. 3: Flammable liquids – Category 3</p> <p>Acute Tox. 4: Acute toxicity – Category 4</p> <p>Skin Irrit. 2: Skin corrosion/irritation – Category 2</p> <p>Eye Irrit. 2: Serious eye damage/eye irritation – Category 2</p> <p>STOT SE 3: Specific target organ toxicity (single exposure) – Category 3</p> <p>STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2</p> <p>Asp. Tox. 1: Aspiration hazard – Category 1</p> <p>Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2</p> <p>Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3</p>
--	---

EU